



d ₁	d ₂	h ₁		d ₃	h ₂		h ₃ Adjustable range		for screw	Static load F in kN				Code no. for C-Spanner
		Version			Version		Version			Steel		Stainless Steel		
		low	high		low	high	low	high		F ₁	F ₂	F ₁	F ₂	
25	5,5	27	40	M 15 x 1	31	50	4	10	M 5	40	33,4	27,1	22,24	DIN 1810-A25-28
25	6,6	27	40	M 15 x 1	31	50	4	10	M 6	40	30,7	27,1	20,26	DIN 1810-A25-28
32	6,6	32	49	M 20 x 1	37	63	5	14	M 6	65	55,7	43,4	36,56	DIN 1810-A30-32
32	9	32	49	M 20 x 1	37	63	5	14	M 8	65	48	43,4	30,86	DIN 1810-A30-32
32	11	32	49	M 20 x 1	37	63	5	14	M 10	65	37,9	43,4	23,41	DIN 1810-A30-32
45	11	41	61	M 30 x 1,5	48	79	7	18	M 10	120	92,9	84	64,01	DIN 1810-A45-50
45	13,5	41	61	M 30 x 1,5	48	79	7	18	M 12	120	80,4	84	54,82	DIN 1810-A45-50
45	17,5	41	61	M 30 x 1,5	48	79	7	18	M 16	120	45,5	84	28,90	DIN 1810-A45-50
58	17,5	53	79	M 40 x 1,5	62	102	9	23	M 16	210	136	148	92,90	DIN 1810-A58-62
58	22	53	79	M 40 x 1,5	62	102	9	23	M 20	210	90	148	59,08	DIN 1810-A58-62
58	26	53	79	M 40 x 1,5	62	102	9	23	M 24	210	37	148	20,30	DIN 1810-A58-62
70	22	61	94	M 50 x 1,5	71	123	10	29	M 20	330	210	225	136,08	DIN 1810-A68-75
70	26	61	94	M 50 x 1,5	71	123	10	29	M 24	330	157	225	97,30	DIN 1810-A68-75
70	33	61	94	M 50 x 1,5	71	123	10	29	M 30	330	53	225	20,60	DIN 1810-A68-75
80	26	67	105	M 60 x 2	79	144	12	39	M 24	495	322	323	195,30	DIN 1810-A80-90
80	33	67	105	M 60 x 2	79	144	12	39	M 30	495	218	323	118,60	DIN 1810-A80-90
80	39	67	105	M 60 x 2	79	144	12	39	M 36	495	101	323	38,20	DIN 1810-A80-90

Specification

- Steel, 1.7225 (42 CrMo 4 V) zinc plated, blue passivated **ST**
- Stainless Steel AISI 303 (X 10 CrNiS 18-9) **NI**
- F₁: max. total load
- F₂: max. total load after deduction of the max. preload
 - for screws 8.8, μ = 0,125 (Steel)
 - for screws 6.8, μ = 0,14 (Stainless Steel)

• RoHS compliant

Accessory

- C-Spanner DIN 1810 (code no. see table)



Information

Levelling sets GN 350.5 are used for levelling, adjusting and linking operations. The spherical washer allows precise installation of two non parallel planes at a required gradient up to ≈ 4°.

They comprise a threaded upper sleeve and a female threaded lower sleeve. The fine thread allows a stepless and precise setting and locking using the C-Spanner DIN 1810. A locking ring serves as a height limiter for the max. height.

see also...

- Levelling sets GN 350 (long version) → Page 548

How to order

GN350.5-45-11-41-NI

1	d ₁
2	d ₂
3	h ₁
4	Material

2.1
2.2
2.3
2.4
2.5
2.6
2.7
2.8
2.9