


Example of application



ROSTREF®
Inox
Stainless
Steel

3 Form

- A** with 2 key rings
- B** with tab and key ring
- C** with 2 tabs
- D** without key ring and without tab

1 **2**

Length l	d ₁	d ₂	Static load in N ≈		Type A and Type B are suitable for ball lock pins and locking pins with axial lock	
			with key ring	without key ring		
150	14 *	1	50	1800	* GN 113.1, GN 113.3, GN 113.4 GN 113.7, GN 113.8, GN 214.2, GN 214.3, GN 214.6 for pins Ø 5, Ø 6, Ø 8 and	
150	18 **	1,3	90	1800		
150	24	1,5	100	1800		
150	30	1,8	120	1800		
200	14 *	1	50	1800		
200	18 **	1,3	90	1800		
200	24	1,5	100	1800		
200	30	1,8	120	1800		
320	14 *	1	50	1800		
320	18 **	1,3	90	1800		
320	24	1,5	100	1800	* GN 113.5, GN 113.6, GN 114.2 GN 114.3, GN 114.6, GN 124.1 GN 124.2 for all pins	
320	30	1,8	120	1800		
500	14 *	1	50	1800		
500	18 **	1,3	90	1800		
500	24	1,5	100	1800		
500	30	1,8	120	1800		
500	14 *	1	50	1800		**GN 113.1, GN 113.3, GN 113.4 GN 113.7, GN 113.8, GN 214.2, GN 214.3, GN 214.6 for pins Ø 10, Ø 12, Ø 16, Ø 20
500	18 **	1,3	90	1800		
500	24	1,5	100	1800		
500	30	1,8	120	1800		

Specification

- Retaining cable
Stainless Steel A2
coated with clear plastic (PVC)
- Tab
Stainless Steel AISI 304
- Key ring
Stainless Steel AISI 301
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

Accessory

- Single key rings are supplied with code no. GN 111.3

Information

The key rings are supplied fixed to the Stainless Steel-Retaining cable. In type A, both rings have the same diameter d₁.

The details on load-bearing capacity are guide values given without warranty.

see also...

- *Spiral retaining cables* GN 111.4 → Page XYZ

How to order (Type C and D)	1 Length l
	3 Type
GN 111.2-200-C	

How to order (Type A and B)	1 Length l
	2 d ₁
	3 Type
GN 111.2-150-14-B	

2.1
2.2
2.3
2.4
2.5
2.6
2.7
2.8
2.9