


ROSTFREI
Inox
Stainless
Steel



d ₀ Ball joint-Ø GN 784	d ₁	d ₂	d ₃	d ₄	d ₅	h ₁	h ₂	m	s
23	42	32,5	4,5	M 5	2	6	8,5	7	2,5
31	49	40	4,5	M 6	3	6	10,5	9	3
39	60	50	5,5	M 8	4	10	14,6	12	4
49	70	60	5,5	M 8	4	10	14,6	16	4

Specification

- Stainless Steel AISI 304 matte, tumbled finish **MT**
- Countersunk screw DIN 7991 Stainless Steel AISI 304
- Half-length tapered groove pin DIN 8745 Stainless Steel AISI 304
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**



Information

The GN 784.1 flanges are mounted from below onto the GN 784 mounting clamps with swivel ball joint. A half-length tapered groove pin prevents any rotation.

The flange enables the mounting clamps with swivel ball joint to be mounted on the upper surface. The d₂ section with the three d₃ drill holes is configured so that standard screws with washers can be used.

The half-length tapered groove pin is mounted on the flange. The countersunk screw is included separately.

see also...

- *Mounting clamps with swivel ball joint GN 784* → Page XYZ

How to order

GN 784.1-70-MT

1 d₁

2 Finish