



4 Type
A without rubber underlay
G with rubber underlay

1 d ₁	2 d ₂	3 l ₁			l ₂	l ₃	A/F	t min.	Static load in kN (see information)
25	M 6*	-	-	-	18,5	4	12	9	5
25	M 8	40	50	63	18,5	4	12	9	5
32	M 8	40	50	63	22,5	5	12	9	7
32	M 10	50	63	80	22,5	5	15	10,5	7
40	M 10	50	63	80	25,5	6	15	10,5	10
40	M 12	63	80	100	25,5	6	17	11,5	10
50	M 10	50	63	80	27,5	7	15	10,5	10
50	M 12	63	80	100	27,5	7	17	11,5	10
60	M 12	63	80	100	35,5	8,5	17	11,5	14
60	M 16	80	100	125	35,5	8,5	24	16	14
60	M 20**	98	138	158	35,5	8,5	24	-	14
60	M 24**	98	138	158	35,5	8,5	24	-	14

* only GN 343.3 (female thread) ** only GN 343.4 (threaded stud)

Specification

- Foot
 Plastic (Polyamide PA)
 - glass fibre reinforced
 - black, matt
 - temperature resistant up to 100 °C
- Threaded bush / stud
 Steel
 - Tensile strength class 5.8 (500 N/mm²)
 - zinc plated, blue passivated
- Hexagon nut ISO 4032
 Steel
 zinc plated, blue passivated
- Rubber underlay (NBR)
 70 Shore A, black
- RoHS compliant

On request

- ESD version
 (conductive plastic cap to avoid electrostatic charging)

Information

Levelling feet GN 343.3 / 343.4 are capable of withstanding high static loads through the use of a high density plastic material coupled with a design which distributes the load over a larger area. Exceeding the static values specified in the above table could lead to failure of the plastic component. The above values have been arrived at by a series of load tests whereby a defined number of levelling feet were subjected to a vertical load over a defined period. Levelling feet GN 343.3 / GN 343.4 are supplied assembled, but are removable.

Levelling foot with female thread GN 343.3-32-M10-A	1 d ₁
	2 d ₂
	3 l ₁
	4 Type

Levelling foot with threaded stud GN 343.4-60-M16-80-G	1 d ₁
	2 d ₂
	3 l ₁
	4 Type