

4 Type
SV with damping element

1 **2** **3**

d ₁	d ₂	l ₁	d ₃	l ₂	l ₃	l ₄	compression in N/mm ²			A/F	t	Area damping element in mm ²	Load in N at compression 0,4 N/mm ² (see information)
							0	0,4	0,6				
32	M 10	50	80	30	29	11	5,5	3,8	2,7	15	10,5	707	280
40	M 12	63	100	38	30	9,5	6	4,3	3,3	17	11,5	1134	450
50	M 12	63	100	48	30,5	9	6,5	4,9	3,9	17	11,5	1809	720
60	M 16	80	125	58	37,5	10	7	5,5	4,4	24	16	2641	1050

Specification

- Steel
 - Tensile strength class 5.8 (500 N/mm²)
 - zinc plated, blue passivated
- Damping element
 - Elastomer (PUR)
 - Sylomer SR 450-12
 - anti-slip, glued
 - grey
 - oil resistant
 - Operating range from -30 °C up to +70 °C
- Hexagon nut ISO 4032
 - Steel zinc plated, blue passivated
- *Elastomer characteristics* → page 1140
- RoHS compliant

Information

The specified load in the above table of the levelling feet GN 342.1 / GN 342.2 is a recommendation up to which the damping element can be **permanently** subjected.


This static load equals a thrust on the area of 0,4 N/mm², at which the damping material reaches its optimum dynamic damping ability. This also takes into account an additional load up to 0,6 N/mm² in the event of a dynamic load.

Levelling feet GN 342.1 / GN 342.2 cannot be disassembled.

Levelling foot with female thread	1	d ₁
GN 342.1-32-M10-SV	2	d ₂
	4	Type

Levelling foot with threaded stud	1	d ₁
GN 342.2-50-M12-63-SV	2	d ₂
	3	l ₁
	4	Type

Vibration absorption - Performance graph



When using levelling feet GN 342.1 / GN 342.2 the following differentiation in vibration absorption is made:

Active vibrations:

Vibrations transmitted to surroundings or associated equipment from working machinery for example.

Passive vibrations:


Vibrations transmitted to equipment or parts from vibrating surroundings or bases.

The efficiency of vibration absorption is dependent upon the interference frequency of the vibration to be absorbed as well as on the resonant frequency of the damping element itself.

A vibration absorbing effect is only achieved when the interference frequency is greater than $\sqrt{2}$ -times the resonant frequency of the damping element. The greater the difference $[\Delta]$ between the two, the better the damping effect.

The resonant frequency of the damping pad is dependant upon type (composition) of the material cross section and the static load.

The graphs on the left show all the required data of the standard material (SR 450-12) of the damping element. Damping elements with other absorption properties are available on request.



Parameter: Power transmission in dB, Degree of isolation in %

Example

Assume a load per levelling foot: 400 N

Compression levelling foot $d1 = 32$

$$\frac{400 \text{ N}}{707 \text{ mm}^2} = 0,57 \text{ N/mm}^2$$

Compression levelling foot $d1 = 40$

$$\frac{400 \text{ N}}{1134 \text{ mm}^2} = 0,34 \text{ N/mm}^2$$

Therefore levelling feet with $d1=40$, that exert a pressure of $0,4 \text{ N/mm}^2$ should be preferred.

The above graph shows:

Resonant frequency with compression $0,34 \text{ N/mm}^2$: $17,5 \text{ Hz}$

The lower graph shows:

Degree of isolation at 66 Hz interference frequency (P1): 92%

Degree of isolation at 98 Hz interference frequency (P2): 97%

At approximately 200 Hz interference frequency the degree of isolation is 100% .

2.1
2.2
2.3
2.4
2.5
2.6
2.7
2.8
2.9