



4 Type (Base plate)

- A1** Steel, zinc plated rubber, inlaid black
- A2** Steel, zinc plated rubber, inlaid white

| d ₁ | d ₂ | l ₁ | Version S / SK | | | | | | Version U / UK | | | | | | l ₇ | h ₁ | h ₂ | s |
|----------------|----------------|----------------|----------------|----|-----|-----|-----|-----|----------------|-----|-----|-----|------|-----------|----------------|----------------|----------------|---|
| | | | 40 | 50 | 63 | - | - | - | 75 | 100 | 125 | 150 | 200 | Version X | | | | |
| 50 | M 8 | 8 | 40 | 50 | 63 | - | - | - | - | - | - | 37 | 14,5 | 3,5 | 3 | | | |
| 50 | M 10 | 8 | 50 | 60 | 80 | 100 | - | - | - | - | - | 40 | 14,5 | 3,5 | 3 | | | |
| 50 | M 12 | 8 | 60 | 80 | 100 | 125 | - | - | - | - | - | 43 | 14,5 | 3,5 | 3 | | | |
| 50 | M 16 | 8 | - | - | - | - | 75 | 100 | 125 | 150 | 200 | 49 | 14,5 | 3,5 | 3 | | | |
| 60 | M 8 | 10 | 40 | 50 | 63 | - | - | - | - | - | - | 38 | 16 | 4 | 3 | | | |
| 60 | M 10 | 10 | 50 | 60 | 80 | 100 | - | - | - | - | - | 41 | 16 | 4 | 3 | | | |
| 60 | M 12 | 10 | 60 | 80 | 100 | 125 | - | - | - | - | - | 45 | 16 | 4 | 3 | | | |
| 60 | M 16 | 10 | - | - | - | - | 75 | 100 | 125 | 150 | 200 | 50 | 16 | 4 | 3 | | | |
| 80 | M 8 | 12 | 40 | 50 | 63 | - | - | - | - | - | - | 40 | 18 | 5 | 3 | | | |
| 80 | M 10 | 12 | 50 | 60 | 80 | 100 | - | - | - | - | - | 43 | 18 | 5 | 3 | | | |
| 80 | M 12 | 12 | 60 | 80 | 100 | 125 | - | - | - | - | - | 47 | 18 | 5 | 3 | | | |
| 80 | M 16 | 12 | - | - | - | - | 75 | 100 | 125 | 150 | 200 | 52 | 18 | 5 | 3 | | | |
| 80 | M 20 | 12 | - | - | - | - | 75 | 100 | 125 | 150 | 200 | 60 | 18 | 5 | 3 | | | |
| 80 | M 24 | 12 | - | - | - | - | 100 | 125 | 150 | 200 | - | - | 18 | 5 | 3 | | | |
| 100 | M 8 | 14 | 40 | 50 | 63 | - | - | - | - | - | - | 42 | 20 | 6 | 3 | | | |
| 100 | M 10 | 14 | 50 | 60 | 80 | 100 | - | - | - | - | - | 45 | 20 | 6 | 3 | | | |
| 100 | M 12 | 14 | 60 | 80 | 100 | 125 | - | - | - | - | - | 49 | 20 | 6 | 3 | | | |
| 100 | M 16 | 14 | - | - | - | - | 75 | 100 | 125 | 150 | 200 | 54 | 20 | 6 | 3 | | | |
| 100 | M 20 | 14 | - | - | - | - | 75 | 100 | 125 | 150 | 200 | 62 | 20 | 6 | 3 | | | |
| 100 | M 24 | 14 | - | - | - | - | 100 | 125 | 150 | 200 | - | - | 20 | 6 | 3 | | | |
| 120 | M 20 | 16 | - | - | - | - | 100 | 125 | 150 | 200 | - | 65 | 22 | 6 | 4 | | | |
| 120 | M 24 | 16 | - | - | - | - | 100 | 125 | 150 | 200 | - | - | 22 | 6 | 4 | | | |
| 120 | M 30 | 16 | - | - | - | - | 100 | 125 | 150 | 200 | - | - | 22 | 6 | 4 | | | |

Specification

- Base plate, sheet metal
Steel, zinc plated, blue passivated
- Threaded stem
Steel, zinc plated, blue passivated
- Hexagon nut ISO 4032
Steel, zinc plated, blue passivated
- Rubber underlay, inlaid
- black: Perbunan® (NBR)
80±5 Shore A
- white: Santoprene® (TPE)
80±5 Shore A
- Elastomer characteristics → Page 330
- Load rating information → Page 231
- RoHS compliant

Versions of threaded stem

| | | |
|---|---|---|
| <p>5 S without nut SK with nut</p> | <p>5 U without nut UK with nut</p> | <p>5 X with female thread</p> |
| <p>External hexagon at the bottom M 8, M 10, M 12</p> | <p>Hexagon socket at the top Wrench flat at the bottom M 16, M 20, M 24, M 30</p> | <p>External hexagon Female thread M 8, M 10, M 12, M 16, M 20</p> |

| d ₁ | d ₂ | h ₃ | h ₄ | A/F ₁ | A/F ₂ | A/F ₃ | A/F ₇ | t |
|----------------|----------------|----------------|----------------|------------------|------------------|------------------|------------------|----|
| 50 | M 8 | 23 | - | 17 | - | - | 14 | 8 |
| 50 | M 10 | 23 | - | 17 | - | - | 14 | 10 |
| 50 | M 12 | 23 | - | 17 | - | - | 17 | 12 |
| 50 | M 16 | - | 29 | - | 12 | 8 | 22 | 16 |
| 60 | M 8 | 24 | - | 17 | - | - | 14 | 8 |
| 60 | M 10 | 24 | - | 17 | - | - | 14 | 10 |
| 60 | M 12 | 24 | - | 17 | - | - | 17 | 12 |
| 60 | M 16 | - | 30 | - | 12 | 8 | 22 | 16 |
| 80 | M 8 | 26 | - | 17 | - | - | 14 | 8 |
| 80 | M 10 | 26 | - | 17 | - | - | 14 | 10 |
| 80 | M 12 | 26 | - | 17 | - | - | 17 | 12 |
| 80 | M 16 | - | 32 | - | 12 | 8 | 22 | 16 |
| 80 | M 20 | - | 33 | - | 15 | 10 | 27 | 20 |
| 80 | M 24 | - | 36 | - | 19 | 12 | - | - |
| 100 | M 8 | 28 | - | 17 | - | - | 14 | 8 |
| 100 | M 10 | 28 | - | 17 | - | - | 14 | 10 |
| 100 | M 12 | 28 | - | 17 | - | - | 17 | 12 |
| 100 | M 16 | - | 34 | - | 12 | 8 | 22 | 16 |
| 100 | M 20 | - | 35 | - | 15 | 10 | 27 | 20 |
| 100 | M 24 | - | 38 | - | 19 | 12 | - | - |
| 120 | M 20 | - | 39 | - | 15 | 10 | 27 | 20 |
| 120 | M 24 | - | 42 | - | 19 | 12 | - | - |
| 120 | M 30 | - | 46 | - | 24 | 12 | - | - |

Information

Levelling feet GN 30 will be delivered mounted and are not removable.

see also...

- Levelling feet GN 32 (Steel, with fixing lug) → Page 222
- Stainless Steel-Levelling feet GN 31 → Page 220

| | | |
|---|---|----------------------------------|
| <p>How to order</p> <p>GN 30-120-M30-125-A1-UK</p> | 1 | d ₁ |
| | 2 | d ₂ |
| | 3 | l ₁ (l ₇) |
| | 4 | Type (Base plate) |
| | 5 | Version (Stem) |