



**4 Type (Base plate)**

- B1** matt shot-blasted, rubber, inlaid, black
- B2** matt shot-blasted, rubber, inlaid, white
- B3\*** matt shot-blasted, rubber, vulcanised, black
- B4\*** matt shot-blasted, rubber, vulcanised, white
- C3\*** polished, rubber, vulcanised, black
- C4\*** polished, rubber, vulcanised, white

d <sub>1</sub>	d <sub>2</sub>	Version S / SK						Version T / TK and U / UK						Version V / VK						Version W						I <sub>7</sub> <sup>+4,0</sup> <sub>0</sub>	t	A/F <sub>7</sub>		
		40	50	63	-	-	-	75	100	125	150	200	-	-	-	75	100	125	150	200	75	100	125	150	125				150	175
50	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	37	8	14	
50	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	40	10	14	
50	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	43	12	17	
50	M 16	-	-	-	-	75	100	125	150	200	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	49	16	22	
60	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	38	8	14	
60	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	41	10	14	
60	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	45	12	17	
60	M 16	-	-	-	-	75	100	125	150	200	75	100	125	150	123	148	173	198	50	16	22	-	-	-	-	-	49	16	22	
80	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	40	8	14	
80	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	43	10	14	
80	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	47	12	17	
80	M 16	-	-	-	-	75	100	125	150	200	75	100	125	150	125	150	175	200	52	16	22	-	-	-	-	-	52	16	22	
80	M 20	-	-	-	-	75	100	125	150	200	100	125	150	200	149	174	199	249	60	20	27	-	-	-	-	-	60	20	27	
80	M 24	-	-	-	-	100	125	150	200	-	100	150	200	-	174	224	274	-	-	-	-	-	-	-	-	-	-	-	-	-
100	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	42	8	14	
100	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	45	10	14	
100	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	49	12	17	
100	M 16	-	-	-	-	75	100	125	150	200	75	100	125	150	126	151	176	201	54	16	22	-	-	-	-	-	54	16	22	
100	M 20	-	-	-	-	75	100	125	150	200	100	125	150	200	151	176	201	251	62	20	27	-	-	-	-	-	62	20	27	
100	M 24	-	-	-	-	100	125	150	200	-	100	150	200	-	176	226	276	-	-	-	-	-	-	-	-	-	-	-	-	-
120	M 20	-	-	-	-	100	125	150	200	-	-	-	-	-	-	-	-	-	65	20	27	-	-	-	-	-	65	20	27	
120	M 24	-	-	-	-	100	125	150	200	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
120	M 30	-	-	-	-	100	125	150	200	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

\* only available for the dimensions d<sub>1</sub> = 60, 80 and 100.

**Specification**

- Base plate, sheet metal  
Stainless Steel AISI 304
- Threaded stem  
Stainless Steel AISI 303
- Hexagon nut ISO 4032  
Stainless Steel AISI 304
- Rubber underlay, inlaid
  - black: Perbunan® (NBR) 80±5 Shore A
  - white: Santoprene® (TPE) 80±5 Shore A
- Rubber underlay, vulcanised
  - 80±5 Shore A
  - black: Perbunan® (NBR)
  - white: Perbunan® (NBR)
- RoHS compliant

**Versions of threaded stem**

<p><b>S</b> without nut <b>SK</b> with nut</p>	<p><b>T</b> without nut <b>TK</b> with nut</p>	<p><b>U</b> without nut <b>UK</b> with nut</p>
<p>External hexagon at the bottom M 8, M 10, M 12</p>	<p>Wrench flat at the bottom M 16, M 20, M 24, M 30 „not dipping“ version</p>	<p>Hexagon socket at the top Wrench flat at the bottom M 16, M 20, M 24, M 30</p>
<p><b>V</b> without nut <b>VK</b> with nut</p>	<p><b>W</b> with adjustable sleeve</p>	<p><b>X</b> with female thread</p>
<p>External hexagon at the top Wrench flat at the bottom M 16, M 20, M 24</p>	<p>Covered thread (see information) Wrench flat at the bottom M 16, M 20, M 24</p>	<p>External hexagon Female thread M 8, M 10, M 12, M 16, M 20</p>

d <sub>1</sub>	d <sub>2</sub>		d <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub> <sup>+4,0</sup>	h <sub>4</sub> <sup>+4,0</sup>	h <sub>5</sub> <sup>+4,0</sup>	l <sub>4</sub>	l <sub>5</sub>	l <sub>6</sub>	s	A/F <sub>1</sub>	A/F <sub>2</sub>	A/F <sub>3</sub>	A/F <sub>4</sub>	A/F <sub>5</sub>	A/F <sub>6</sub>	
50	M 8	M 10	M 12	-	14,5	3,5	23	-	-	-	-	3	17	-	-	-	-	-	
50	M 16	-	-	-	14,5	3,5	-	29	-	-	-	3	-	12	8	-	-	-	
60	M 8	M 10	M 12	-	16	4	24	-	-	-	-	3	17	-	-	-	-	-	
60	M 16	-	-	24	16	4	-	30	27	45	45	29	3	-	12	8	10	12	20
80	M 8	M 10	M 12	-	18	5	26	-	-	-	-	3	17	-	-	-	-	-	
80	M 16	-	-	24	18	5	-	32	29	45	45	29	3	-	12	8	10	12	20
80	M 20	-	-	30	18	5	-	33	30	56	56	36	3	-	15	10	13	16	24
80	M 24	-	-	35	18	5	-	36	33	67	67	42	3	-	19	12	17	20	30
100	M 8	M 10	M 12	-	20	6	28	-	-	-	-	3	17	-	-	-	-	-	
100	M 16	-	-	24	20	6	-	34	31	45	45	29	3	-	12	8	10	12	20
100	M 20	-	-	30	20	6	-	35	32	56	56	36	3	-	15	10	13	16	24
100	M 24	-	-	35	20	6	-	38	35	67	67	42	3	-	19	12	17	20	30
120	M 20	-	-	-	22	6	-	39	-	-	-	4	-	15	10	-	-	-	
120	M 24	-	-	-	22	6	-	42	-	-	-	4	-	19	12	-	-	-	
120	M 30	-	-	-	22	6	-	46	-	-	-	4	-	24	12	-	-	-	

**Information**

GN 31 Stainless Steel-Levelling feet with vulcanised rubber (Type B3, B4, C3 and C4) and screw version W feature fewer dead spots owing to their construction method and are also easier to clean.

Stainless Steel-Levelling feet GN 31 will be delivered mounted and are not removable.

Load rating information → Page 232

see also...

- *Stainless Steel-Levelling feet GN 33 (with fixing lug)* → Page 224
- *Levelling feet GN 30 (Steel, zinc plated)* → Page 218

**How to order**

1	d <sub>1</sub>
2	d <sub>2</sub>
3	l <sub>1</sub> (l <sub>2</sub> , l <sub>3</sub> , l <sub>7</sub> )
4	Type (Base plate)
5	Version (Stem)

GN 31-80-M20-100-C4-U