



4 Type
A 2x2 threaded blind bores

2

3

l_1	l_2	d_1	d_2	h_1	h_2	l_3	l_4	l_5	m_1	m_2	t
40	42	M 5	6	14	8	34	12	18	25	25	5
50	52	M 6	6	18	10	39	16	21	30	30	6,5
60	62	M 6	8	22	12	47	20	24	36	36	7,5

Specification

1

5

- Zinc die casting **ZD**
- plastic coated black, RAL 9005, textured finish **● SW**
- silver, RAL 9006, textured finish **● SR**
- Pin
- Stainless Steel AISI 303
- Stainless Steel characteristics → Page 334
- RoHS compliant

Information

With their attractive design, hinges GN 138 are suitable for use in plant and machinery where a well-designed and stylish appearance is important.

The concealed and tamper-proof mounting from the rear highlights and enhances the special appearance of the hinge.

The dimensions l_1 / l_2 and the drill hole spacings m_1 / m_2 match the usual hinges GN 237 / GN 237.1 and can replace these.

see also...

- Hinges GN 238 → Main catalogue Page 880
- Hinge GN 139.2 → Page 254

How to order

1	Material
2	l_1
3	l_2
4	Type
5	Colour

GN 138-ZD-50-52-A-SR