

CFP. Hinges with snap-in positions

screw-covers, technopolymer



- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- RH

MATERIAL

Acetal resin based (POM) technopolymer, black colour, matte finish.

ROTATING PIN

Acetal based (POM) technopolymer, black colour.

SCREW-COVERS

Polyester based (PBT) technopolymer, black colour, matte finish, snap-in assembly.

STANDARD EXECUTIONS

- **CFP-SH**: pass-through holes for countersunk head screws.
- **CFP-CH**: pass-through holes for cylindrical head screws.
- **CFP-EH**: pass-through holes for hexagonal head screws.

ROTATION ANGLE (APPROXIMATE VALUE)

Max 195° (-15° and +180° being 0° the condition where the interlocked surfaces are on the same plane).

Do not exceed the rotation angle limit so as not to prejudice the hinge mechanical performance.

This hinge can be used combined with the hinge type CFQ. (see page 955) with the same design, without detent position.

The detent device (ELESA patent) allows four different detent positions of the door (0°, +80°, +120°, +170°).

To choose the convenient type and the right number of hinges for your application, see the Guidelines (see page 952).




RESISTANT TORQUE

All detent positions guarantee a resistant torque of about 1.1 Nm (which is the torque that must be applied to free the detent device of the hinge).

The hinge had been tested with more than 10.000 opening and closing cycles and the value of the resistant torque was unchanged.







FMM design



Resistance tests

AXIAL STRESS		RADIAL STRESS		80° AND 90° ANGLED STRESS		120° ANGLED STRESS		70° ANGLED STRESS		Resistant torque
Maximum working load Ea [N]	Load at breakage Ra [N]	Maximum working load Er [N]	Load at breakage Rr [N]	Maximum working load E80 e E90 [N]	Load at breakage R80 e R90 [N]	Maximum working load E120 [N]	Load at breakage R120 [N]	Maximum working load E170 [N]	Load at breakage R170 [N]	[Nm]
300	1220	350	1970	345	620	285	855	400	1410	1.1



Code	Description	L	B	f	f1	H	h1	h2	h3	b1	d	d3	d4	d5	d6	C# [Nm]	Δ
426311-C9	CFP.50 SH-4-C9	50	45	32	25	14	8	7	-	21.5	8	4.5	8.5	-	-	1.5	17
426312-C9	CFP.50 CH-4-C9	50	45	32	25	14	8	7	4.5	21.5	8	4.5	-	8.5	-	1.5	17
426313-C9	CFP.50 EH-4-C9	50	45	32	25	14	8	7	4.5	21.5	8	4.5	-	-	7	1.5	17

Hinges and connections