



ROSTFREI
Inox
Stainless
Steel

3 Type

C Fixing from the back side

1

2

l ₁		l ₂		b	d ₁	d ₂ Pin	h ₁	h ₂	l ₃	l ₄ max.	l ₅	l ₆ max.	l ₇	m ₁	m ₂	s	t
ST	NI / A4	ST	NI / A4														
45	45	40	40	13	M 6	6	13	13,5	18	6	11	5	10	30	28,2	12	9
50	50	51	51	18	M 8	8	18	18	26	8	14	8	14	29	35	16	11
53	-	40	-	13	M 6	6	13	13,5	26	6	11	5	10	38	28,2	12	9
61	-	51	-	18	M 8	8	18	18	26	8	14	8	14	40	35	16	11

Specification

- Hinge
Steel
zinc plated, blue passivated
- Pin
Brass, nickel plated
- Washer
Brass, nickel plated
- Hexagon nut ISO 4032
Steel zinc plated, blue passivated
- Serrated washer DIN 6797
for securing screws
Steel zinc plated, blue passivated

ST

- Hinge body, pin, washer
- Stainless Steel AISI 303 **NI**
- Stainless Steel AISI 316L **A4**
- Hexagon nut ISO 4032
Stainless Steel AISI 304
- Serrated washer DIN 6797
for securing screws
Stainless Steel AISI 304

• *Stainless Steel characteristics* → Page 334

• **RoHS compliant**

4

Information

Hinges GN 129.2 are used for doors which are flush with the frame on the outside. Once assembled, they cannot be unhinged.

With the fixing from the inside, they are especially suitable for doors and trap doors which must not be detachable from the outside as an anti-tamper device.

see also...

- *Hinges GN 129* → Main catalogue Page 893

How to order

GN 129.2-53-40-C-ST

1	l ₁
2	l ₂
3	Type
4	Material