




**Examples of application**



Latches GN 119



Latches GN 115



Please note: The clamping range A1 ... A9 and/or the latch distance A is reduced by the dimension „b“.

1

2

d	s	b	h <sub>1</sub>	h <sub>2</sub>	Length l	useable for
29	14,5	2	6	11	18,5	GN 115.1 / GN 115.6
36	20,5	2	8	12	23	GN 115 / GN 115.8 / GN 119 / GN 516 / GN 516.1 / GN 516.5

**Specification**

- Plastic (Polyethylene)  
black
- RoHS compliant

**Information**

GN 120 protective caps are used in combination with key-actuated locking devices. These prevent dirt from entering the key mechanism and the locking device and can be mounted as required in a 90° grid pattern together with the housing of the locking device.

GN 120 protective caps are suitable for the following latches:

- Mini-Latches GN 115.1 / GN 115.6 → Page 864
- Latches GN 115 → Page 858 ff.
- Hook-type latches GN 115.8 → Page XYZ
- Latches GN 119 → Page 848 ff.
- Rotary clamping latches GN 516 → Page 852
- Rotary clamping latches GN 516.1 → Page 854
- Stainless Steel-Rotary clamping latches GN 516.5 → Page 855

How to order

GN 120-36-20,5

1 d

2 s