







ROSTFREI
Inox
Stainless
Steel

1 Type

Operation

- VK8** with square spindle A/F8
- SCH** with slot
- VDE** with double bit
- RG** with knurled knob GN 7336
- KG** with wrench
- HG** with lever



2

Latch distance A

19	23	27	31	33	35	37	39	41
----	----	----	----	----	----	----	----	----

Specification

- Stainless Steel
 - Housing AISI 316
 - Locking mechanism AISI 316
 - Bolt AISI 316
 - Latch AISI 304
- all handles (Type RG / KG / HG)
 - Plastic (Polyamide PA)
 - black, matt
 - Cover cap light grey matt
- Protection class: IP 65
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

Accessory

- Key GN 119.2 → Page 870

Information

The Stainless Steel-rotary clamping latches GN 516.5 have a closing mechanism which transfers the rotary movement of the operating element / key into a 90° turn and then into a 6 mm linear stroke.

This mechanism is designed for common applications such as making a tight and vibration-proof interlock in the end position (retaining position) in connection with an elastic element (door / casing seal).

9 latches with different cranks will cover latch distances (retaining zones) of between 19 and 41 mm. If the measured retaining position lies between two latch distances A, the next smaller value must be selected.

The rotary clamping latches GN 516.5 are supplied with the latch enclosed loose.

see also...

- *Technical and assembly instructions* → Page 853
- *Rotary clamping latches GN 516 (Zinc die casting)* → Page 852

How to order

GN 516.5-VK8-19

1	Type
2	Latch distance A