



1 2

d ₁	d ₂	l ₁	l ₂	l ₃	d ₃	s ₁ Height Clamping arm	s ₂	t	for toggle clamps			
									useable thread depth of the clam- ping arm	GN 810 GN 810.1 GN 860 GN 862 GN 862.1	GN 820 GN 820.1 GN 820.2 GN 820.3 GN 820.4	GN 910 GN 910.1
16	M 6	26,5	31 (33)*	7	M 4	14 (16)*	6,5	22 (24)*	125	130	220	-
18	M 8	31	38 (37)**	8	M 5	18 (17)**	8,5	26 (25)**	200	230	-	200
22	M 10	37	45 (47)***	8	M 5	20 (22)***	10,5	28 (22)***	300	355	-	300
24	M 10	41	49	8	M 5	24	10	32	-	-	440	-
26	M 10	39	48	8	M 5	22	12,5	30	400	-	-	-

* Dimension in parentheses applies to GN 860
 ** Dimension in parentheses applies to GN 812, GN 812.1, GN 862 and GN 862.1
 *** Dimension in parentheses applies to GN 812, GN 812.1, GN 860, GN 862 and GN 862.1

Specification

- Steel
zinc plated, blue passivated
- RoHS compliant

Information

GN 801 clamp mounts have been developed for use with toggle clamps that are designed with a forked clamping arm.

The clamp mount can be moved along the clamping arm. Once the desired position is reached, you can secure the mount in place with the clamping screw.

The d₂ thread functions to hold pressure screws, pressure dies and similar devices.

The ideal clamping height can be adjusted without loosening the clamp mount on the forked clamping arm.

see also...

- Holders for clamping bolts GN 809 → Page 770
(for toggle clamps with solid clamping arm)

How to order	1	d ₁
	2	d ₂

GN801-16-M6

2.1
2.2
2.3
2.4
2.5
2.6
2.7
2.8
2.9