



Mounting examples



Type E



Type Z



**3** Type

**E** for one clamping bolt  
**Z** for two clamping bolts

**1** **2**

b -0,2	d <sub>1</sub>	d <sub>2</sub> <sup>H8/h6</sup>	d <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	m <sub>1</sub>	m <sub>2</sub>	m <sub>3</sub>	m <sub>4</sub>	m <sub>5</sub>
32	M 8	7	M 5	10	10	38	17	37	7,5	22	17	15	31,5	17
42	M 10	9	M 6	12	12	54,5	17	50,5	10	30	25	19,5	45,9	23
52	M 12	11	M 8	14	14	63	17	61	13,5	37	30	23,5	53	30
62	M 12	13	M 10	16	16	73,5	20	83	13,5	44	47	27	63,5	40

**Specification**

- Steel C45 blackened finish
- ISO-Fundamental Tolerances → Page 1132
- RoHS compliant

**Information**

The single post bracket / bracket accessories GN 867.1 have been designed for use with pneumatic fastening clamps GN 864.

Bracket accessories with two clamping bolts (Type Z) are preferably used for rigid clamping of sheet metal components. For the same purpose ball point screws GN 605 with serrated ball pads are also suitable.

Cap screws and guide bushings are included.

see also...

- Ball point screws GN 605 → Page 524

How to order

**GN867.1-42-M10-Z**

<b>1</b>	<b>b</b>
<b>2</b>	<b>d<sub>1</sub></b>
<b>3</b>	<b>Type</b>

2.1  
2.2  
2.3  
2.4  
2.5  
2.6  
2.7  
2.8  
2.9