




2 Type

- R Clamping jaws at right angle to clamping arm
- P Clamping jaws parallel to clamping arm


Mounting examples



Type E



Type P



b -0,2	d ₁	d ₂ H8 h8	d ₃	d ₄ H8 h8	h ₁	h ₂	h ₃	l ₁	l ₂	l ₃ Type R	Type P	l ₄	l ₅ Type R	Type P	l ₆	m ₁	m ₂	m ₃	m ₄	m ₅
32	M 6	9	M 5	7	10	10	10	38	55	37	37	13	18,5	18,5	7,5	22	17	15	31,5	17
42	M 8	11	M 6	9	12	12	14	54,5	77,5	50,5	50,5	17	23,5	23,5	10	30	25	19,5	45,9	23
52	M 10	13	M 8	11	14	14	16	63	93	61	61	20	28	28	13,5	37	30	23,5	53	30
62	M 10	13	M 10	13	16	16	18	73,5	113,5	83,5	85,5	20	27	29	13,5	44	47	27	62,5	40

Specification

- Steel C45 blackened finish
- ISO-Fundamental Tolerances → Page 1132
- RoHS compliant

Information

The bracket / double post bracket accessories GN 868.1 have been designed for use with pneumatic fastening clamps GN 864.

Bracket / double post bracket accessories are equally precisely positioned on the clamping arm as are the jaw block accessories GN 872 on the holders themselves.

Cap screws and guide bushings are included.

see also...

- Clamping jaws blank GN 872 → Page 788

How to order

GN868.1-42-P

- 1 b
- 2 Type