



 Rost frei
 Inox
 Stainless
 Steel

4 Type

- A** without sealing
B with sealing

1

2

| d ₁ | k | d ₂ | d ₃ | d ₄ | Length l | m | t | x ₁ | x ₂ | y ₁ | y ₂ |
|----------------|-----------------|----------------|-----------------|----------------|----------|----|-----|----------------|----------------|----------------|----------------|
| Bore B | Clamping length | | Clamping thread | | | | | | | | |
| B 30 | 50 | 6,5 | M 8 | 37 | 36 | 35 | 6,5 | 60 | 42 | 60 | 42 |

Specification

- Stainless Steel
 - AISI CF-8
 - matt shot-blasted
- Clamping bores mechanically machined
- Carriage bolt DIN 603 Stainless Steel A2
- Cap nuts DIN 917 Stainless Steel A2
- Sealings
 - Washers
Plastic (Polyacetal POM)
 - Edge ring
Silicon, 40 ... 60 Shore A
- Stainless Steel characteristics → Page 334
- RoHS compliant

Information

The clamping bores of the Stainless Steel-Base plate connector clamps GN 163.5 are mechanically machined and designed for construction tubing GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The shape of the clamping screws / nuts prevents the formation of wetness due to dammed-up water. The designs with sealing (Type B) also seals bore holes and threads.

see also...

- Stainless Steel-Construction tubes GN 990
→ Main Catalogue Page 1027
- Stainless Steel-Base plate connector clamps GN 162 (Bore-Ø B12 ... B20)
→ Main Catalogue Page 988
- Stainless Steel-Two-way connector clamps GN 132.5 → Page 286
- Stainless Steel-T-angle connector clamps GN 192.5 → Page 290

How to order

GN 163.5-B30-50-B

- | | |
|---|----------------|
| 1 | d ₁ |
| 2 | k |
| 3 | Type |