



ROSTFREI  
Inox  
Stainless  
Steel

- 3 Identification No.**  
**2** with 2 Stainless Steel-Clamping screws DIN 912

<b>1</b> $d_1$ Bore B without slide bushing		<b>2</b> $d_2$ Bore G with slide bushing		$d_3$ Clamping bore B	$d_4$ Clamping thread	Mounting screw on the follower	$k_1$ Clamping length	$k_2$ Clamping length	Length $l$	$m$	Clamping kit for $d_3$
B 18	G 18	B 18	M 6	M 3	25	25	61	39	GN 911-M6-22	GN 911.3-M6-22	

**Specification**

- Aluminium plastic coated black, RAL 9005, textured finish **● SW**
- Stainless Steel AISI CF-8 **NI**
  - matt shot-blasted
  - Bore only with slide bushing (G18)
- Guide bores / Clamping bores mechanically machined
- Slide bushing Polyamide
- Socket cap screws DIN 912 Stainless Steel AISI 304
- Hexagon nuts DIN 985 Stainless Steel AISI 304
- Stainless Steel characteristics → Page 1144
- RoHS compliant

**Accessory**

- Clamping kits GN 911 / GN 911.3 → Page 1031

**Information**

GN 191.1 T-angle linear actuator connectors are normally supplied **mounted** only in connection with a linear actuator and for function control.

By means of the clamping screw on the guide bore  $d_1$  the movement can either be set or the linear actuator connector can be clamped (after setting of final adjustment).

The standard version of the clamping screws are socket cap screws with hexagonal socket DIN 912. They can be replaced by clamping kits GN 911 / GN 911.3 (article code see table of dimensions).

see also...

- Construction tubes GN 990 → Page 1027
- Linear actuators GN 291 → Page 1036
- Linear actuators GN 292 → Page 1038

How to order (Aluminum)	<b>1</b> $d_1$
	<b>2</b> $d_2$
<b>GN 191.1-G18-B18-2-SW</b>	<b>3</b> Identification No.
	<b>4</b> Finish

How to order (Stainless Steel)	<b>1</b> $d_1$
	<b>2</b> $d_2$
<b>GN 191.1-G18-B18-2-NI</b>	<b>3</b> Identification No.
	<b>4</b> Material