



ROSTFREI
Inox
Stainless
Steel

4 Type
A without sealing
B with sealing

1 d_1 Bore B	2 d_2 Bore B	3 k_1 Clamping length	d_3 Clamping thread	k_2	l_1	l_2	m
B 30	B 30	37	M 8	42	96	35	60
B 50	B 50	65	M 10	75	151,5	48,5	103

Specification

- Stainless Steel
 - AISI CF-8
 - matt shot-blasted
- Clamping bores mechanically machined
- Carriage bolt DIN 603 Stainless Steel A2
- Cap nuts DIN 917 Stainless Steel A2
- Sealings
 - Washers Plastic (Polyacetal POM)
 - Edge ring Silicon, 40 ... 60 Shore A
- Stainless Steel characteristics → Page XYZ
- RoHS compliant

Information

The clamping bores of GN 192.5 Stainless Steel-T-angle connector clamps are mechanically machined and designed for construction tubing GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The shape of the clamping screws / nuts prevents the formation of wetness due to dammed-up water. The designs with sealing (Type B) also seals bore holes and threads.

see also...

- Stainless Steel-Construction tubes GN 990 → Page 1027

How to order

1	d_1
2	d_2
3	k_1
4	Type

GN 192.5-B30-B30-37-A