


3 Identification No.
2 with Stainless Steel-Clamping screw DIN 912



1 **2**

d₁ Bore B for clamping-Ø	d₂ Bore B for sensor	b Swivel width	d₃	d₄ Clamping thread	k	Length l	m	t -0,5	Clamping kit for d ₄
B 12	B 12	B 18	25	M 6	25	64	29,5	11	
B 14	B 12	B 18	25	M 6	25	64	29,5	11	GN 911-M6-22
B 16	B 12	B 18	25	M 6	25	64	29,5	11	GN 911-M6-22
B 18	B 12	B 18	25	M 6	25	64	29,5	11	GN 911-M6-22

Specification

- Aluminum plastic coated black, RAL 9005, textured finish **SW**
- Clamping bores mechanically machined
- Socket cap screws DIN 912 Stainless Steel AISI 304
- Hexagon nuts DIN 985 Stainless Steel AISI 304
- *Stainless Steel characteristics* → Page 334
- **RoHS compliant**

Accessory

- Clamping kits GN 911 → Page 1031

4

Information

The clamping bore of GN 273.4 sensor holders is mechanically machined and designed for construction tubes GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The standard version of the clamping screw is a socket cap screw with hexagonal socket DIN 912. It can be replaced by a clamping kit GN 911 (article code see table of dimensions).

The Aluminum design guarantees a highly safe and secure clamping action and safe positioning.

see also...

- *Construction tubes GN 990* → Page 1027
- *Retaining rods / Retaining tubes GN 480.1* → Page XYZ
- *Clamp mountings GN 478 (for sensor holders GN 479)* → Page 1081

How to order

1	d₁
2	d₂
3	Identification No.
4	Finish

GN 273.4-B14-B18-2-SW