



Type **OZ**
without centring step



- 2** Type
OZ without centring step
- 3** Identification no.
2 with Stainless Steel-
Clamping screw DIN 912

1 **1**

d₁ Bore B	s₁ Square V	b Swivel width	d₂	d₃ Clamping thread	d₄	k Clamping length	l₁	l₂	m	s₂	t	Clamping kits for d ₃
B 40	V 40	65	10,5	M 10	M 10	76	166,5	70	85	17	35	GN 911-M10-63
B 42	-	65	10,5	M 10	M 10	76	166,5	70	85	17	35	GN 911-M10-63
B 45	V 45	65	10,5	M 10	M 10	76	166,5	70	85	17	35	GN 911-M10-63
B 48	-	65	10,5	M 10	M 10	76	166,5	70	85	17	35	GN 911-M10-63
B 50	V 50	65	10,5	M 10	M 10	76	166,5	70	85	17	35	GN 911-M10-63

Specification

- Aluminum
 - plastic coated
black, RAL 9005, textured finish **● SW**
 - blank **○ BL**
matt shot-blasted
- Clamping bore not machined
- Socket cap screws DIN 912
Stainless Steel AISI 304
- Hexagon nuts DIN 985
Stainless Steel AISI 304
- Stainless Steel characteristics → Page 1144
- RoHS compliant

Accessory

- Clamping kits GN 911 → Page 1031

Information

The clamping bore of GN 279 swivel clamp connectors is not machined and designed for construction tubes GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The square designs are also suitable for use in **profile systems**.

The standard version of the clamping screws are socket cap screws with hexagonal socket DIN 912. They can be replaced by clamping kits GN 911 (article code see table of dimensions).

Two GN 279 swivel clamp connectors can be combined to GN 289 swivel clamp connector joints.

GN 279 swivel clamp connectors can be assembled with swivel clamp connectors GN 272, GN 274 and GN 276 to create swivel clamp connector joints.

see also...

- Construction tubes GN 990 → Page 1027
- Swivel clamp connector joints GN 289 → Page 1023

How to order

GN 279-V40-OZ-2-BL

- | | |
|----------|--------------------------------------|
| 1 | s₁ (d₁) |
| 2 | Type |
| 3 | Identification no. |
| 4 | Finish |