



2 Identification No.

2 with 2 Stainless Steel-Clamping screws DIN 912



d ₁ Bore B	b Swivel width	d ₂	d ₃ Clamping thread	k	l ₁	l ₂	m ₁	m ₂	t	x ₁	x ₂	y	Clamping kit for d ₃
B 12	25	5,5	M 6	25	72,5	34,5	24	48,5	7	50	38	35	GN 911-M6-22
B 14	25	5,5	M 6	25	72,5	34,5	24	48,5	7	50	38	35	GN 911-M6-22
B 16	25	5,5	M 6	25	72,5	34,5	24	48,5	7	50	38	35	GN 911-M6-22
B 18	25	5,5	M 6	25	72,5	34,5	24	48,5	7	50	38	35	GN 911-M6-22

Specification

- Aluminum
 - plastic coated
 - black, RAL 9005, textured finish ● **SW**
 - blank ○ **BL**
 - matt shot-blasted
- Clamping bore mechanically machined
- Socket cap screws DIN 912
Stainless Steel AISI 304
- Hexagon nuts DIN 985
Stainless Steel AISI 304
- Stainless Steel characteristics → Page 1144
- RoHS compliant

Accessory

- Clamping kits GN 911 → Page 1031



Information

GN 281 swivel clamp connector joints are an assembly of the swivel clamp connectors GN 271 and GN 275.

The clamping bore is mechanically machined and designed for construction tubes GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The standard version of the clamping screws are socket cap screws with hexagonal socket DIN 912. They can be replaced by clamping kits GN 911 (see table of dimensions).

see also...

- Construction tubes GN 990 → Page 1027
- Swivel clamp connector bases GN 271 → Page 1004
- Swivel clamp connectors GN 275 → Page 1008

How to order

GN281-B14-2-BL

1	d ₁
2	Identification No.
3	Finish