


3 Identification No.
2 with 3 Stainless Steel-Clamping screws DIN 912

1 d₁ Bore B	2 d₂ Bore B	b Swivel width	d₃ Clamping thread	k₁	k₂	l₁	l₂	m₁	m₂	Clamping kit for d ₃ 
B 12	B 12	25	M 6	25	25	100	34,5	29,5	48,5	GN 911-M6-22
B 14	B 14	25	M 6	25	25	100	34,5	29,5	48,5	GN 911-M6-22
B 16	B 16	25	M 6	25	25	100	34,5	29,5	48,5	GN 911-M6-22
B 18	B 18	25	M 6	25	25	100	34,5	29,5	48,5	GN 911-M6-22

Specification

- Aluminum
 - plastic coated black, RAL 9005, textured finish **● SW**
 - blank **○ BL**
 - matt shot-blasted
- Clamping bores mechanically machined
- Socket cap screws DIN 912
Stainless Steel AISI 304
- Hexagon nuts DIN 985
Stainless Steel AISI 304
- Stainless Steel characteristics → Page 1144
- RoHS compliant

Accessory

- Clamping kits GN 911 → Page 1031

Information

GN 283 swivel clamp connector joints are an assembly of the swivel clamp connectors GN 273 and GN 275. Since the swivel clamp connectors have an identical swivel width “b”, all bores “d₁ / d₂” can be combined as required.

The clamping bores are mechanically machined and designed for construction tubes GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The standard version of the clamping screws are socket cap screws with hexagonal socket DIN 912. They can be replaced by clamping kits GN 911 (see table of dimensions).

see also...

- Construction tubes GN 990 → Page 1027
- Swivel clamp connectors GN 273 → Page 1006
- Swivel clamp connectors GN 275 → Page 1008

How to order	
1	d₁
2	d₂
3	Identification No.
4	Finish

GN 283-B12-B14-2-SW