


3 Type

- A** without oil level mark
- B** with oil level mark

1

2

d_1 Window glass	d_2 Bore-Ø	b_{min}	d_3	d_4	$e \pm 0,1$	h	l_1	l_2	Code no. for Pin key for installation 
16	20	9	25	2,2	21	5	15	3,5	GN 537.1-21
22	28	10	35	3	30	6	15	4,5	GN 537.1-30
32	38	12	45	3	40	8	18	5,5	GN 537.1-40
50	58	14	64	3	58,5	10	22	5,5	GN 537.1-58,5

Specification

- Ring nut
Aluminium
- Sight glass
Perspex (PMMA)
temperature resistant up to 80 °C
- Sealing ring
rubber NBR (Perbunan)
- Contrast screen
Plastic
white, with red oil level marks
- *Elastomer characteristics* → Page 1140
- **RoHS compliant**

Accessory

- Pin key for installation GN 537.1
(Code no. see table)

Information

This oil level glass GN 542 does not require a thread.
The oil level sight glass is inserted into the bore d_2 to H11. By simply tightening the ring nut using the pin key the seal is pressed against the contact surface which, at the same time, will hold the sight glass in position. For removal reverse the procedure.
Their application is limited to non-pressurised or only slightly pressurised tanks.

How to order

GN 537-32-38-B

- 1** d_1
- 2** d_2
- 3** Type