




Application example



2

3

l_2	w	b	d	h	l_1	m_1	m_2	s
40	150	12	5,3	7,8	40	25	25	3,5
50	150	15	6,3	9,2	50	30	30	4
60	150	18	8,3	10,9	60	36	36	5

Specification

1

4

- Steel precision casting **ST**
zinc plated, plastic coated
black, RAL 9005, textured finish **SW**
- Elastomer element
- Perbunan® (NBR)
- temperature resistant up to 120 °C
- Hardness 85±5 Shore A
- *Elastomer characteristics*
→ Main catalogue page 1141
- **RoHS compliant**

Information

In terms of their dimensions, rubber bumper stops GN 2374 have been designed as extras for the GN 237 and GN 337 family of hinges. They can also be bolt-attached when mounting the hinge, with an elastomer element limiting the angle of rotation to the value w.

They are mainly used for lighter traps and gates, or when the limit stop is not expected to be exposed to dynamic loads.

see also...

- Hinges GN 237 → Main catalogue page 878
- Hinges GN 337.1 → New products
- Hinges GN 337 → Main catalogue page 877
- Hinges GN 237.1 → Main catalogue page 882

How to order

1 2 3 4
GN 2374-ST-40-150-SW

1	Material
2	l_2
3	w
4	Finish