



- 3 Type**
OS without plastic cap
KS with plastic cap, gliding
KR with plastic cap, non-gliding

1 d_1	2 h	$d_2 +0,2$	$e \approx$	s	Grub screw DIN 6332
50	11,5	9,2	2,5	1,7	M 12
50	13,5	12,5	4	1,7	M 16
60	13,5	12,5	4	1,7	M 16
60	15,5	16,5	4,3	1,7	M 20

Specification

- Steel
zinc plated, blue passivated
- Circlip
Spring steel wire
zinc plated, blue passivated
- Plastic caps:
 - Type KS
Technopolymer (Polyacetal POM)
white (natural colour) RAL 9001
 - Type KR
Elastomer (TPE)
78 Shore A \approx
black
- *Plastic characteristics* \rightarrow Page 1141
- *Elastomer characteristics* \rightarrow Page 1140
- **RoHS compliant**

Information

Foot plates GN 6311.3 are used in connection with screws with pivots (grub screws DIN 6332, tommy screws DIN 6304, DIN 6306).

Owing to the special shape of the immovable retaining ring, the foot plate is easily plugged onto and removed from, the pivot.

see also...

- *Levelling feet GN 6311.4* \rightarrow New products
- *Grub screws DIN 6332* \rightarrow Page 592
- *Tommy screws DIN 6304* \rightarrow Page 256
- *Tommy screws DIN 6306* \rightarrow Page 257

How to order	1 d_1
	2 h
	3 Type
GN6311.3-60-15,5-OS	