



4 Type
B with mounting holes

1 d_1	2 d_2	3 l_1	d_3	d_4	l_2	l_3	k	A/F_1	A/F_2	Static load in kN (see information)	
100	M 16	175	225	28	12	19	35	69	18	22	30
100	M 20	185	235	32	12	24	35	69	24	27	47
100	M 24	185	235	36	12	29	35	69	24	30	67
120	M 16	175	225	28	12	19	35	89	18	22	30
120	M 20	185	235	32	12	24	35	89	24	27	47
120	M 24	185	235	36	12	29	35	89	24	30	67

Specification

- Spindle, adjustable sleeve, foot plate
 - Stainless steel AISI 304
 - turned
- Seals, blue, FDA compliant
 - Sealing ring
NBR, hardness 70 ±5 Shore A
 - Wiper
TPU, hardness 95 ±5 Shore A
 - Joint sealing ring
H-NBR, hardness 85 ±5 Shore A
 - Bottom seal
Silicon, hardness 85 ±5 Shore A
- *Stainless Steel characteristics*
 → Main catalogue Page 1657
- **RoHS compliant**

Information

GN 20 hygienic leveling feet with mounting holes are certified according to EHEDG guidelines and are therefore ideal for use in hygienic applications.

The bottom seal protects the area beneath the foot plate from dirt. For this, the foot must be screwed on using the mounting holes and compressed accordingly. Hygienic fastenings and the correct position of the mounting holes are essential. The sealing ring above the adjustment sleeve enables fastening without dead space. Due to the wiper or the ball seal, the moving components are sealed against the environment.

The high quality finish prevents adherence of dirt and facilitates cleaning.

The values listed in the table for static load capacity refer to a purely vertical load in relation to the leveling foot. Under normal operating conditions bending loads or angular loads are not uncommon and result in a reduction of load capacity, which must be taken into consideration.

How to order	
1 d_1	
2 d_2	
3 l_1	
4 Type	

GN 20-120-M16-175-B