


Counterbored for cap screw DIN 912  
hexagon head screw DIN 931



**3 Type**

- L left indexing cam
- R right indexing cam



Type L  
with retracted plunger

**1**

**2**

d <sub>1</sub> Plunger Bore	s	b +0,3	d <sub>2</sub> +0,2	h <sub>1</sub>	h <sub>2</sub>	k <sub>1</sub>	k <sub>2</sub>	k <sub>3</sub>	l <sub>1</sub> ≈ l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	l <sub>5</sub>	m	A/F	t	Spring load in N ≈				
																Steel		Stainless Steel		
																	initial	end	initial	end
8	20	6,1	6,1	7,5	10	7,5	18	12	68	14	35	37	48	34	10	6,1	16	55	16	45
10	20	6,1	6,1	7,5	10	7,5	18	12	68	14	35	37	48	34	10	6,1	16	55	16	45
12	20	6,1	6,1	7,5	10	7,5	18	12	68	14	35	37	48	34	10	6,1	16	55	16	45
14	20	6,1	6,1	7,5	10	7,5	18	12	68	14	35	37	48	34	10	6,1	16	55	16	45

**Specification**

- Guide  
Steel precision cast  
- zinc plated, blue passivated  
- zinc plated and plastic coated black, textured finish
- Latch  
zinc plated, blue passivated
- Plunger  
Steel, zinc plated, blue passivated
- Spring  
Stainless Steel AISI 301
- Guide / Latch  
Stainless Steel precision casting weldable, AISI 316
- Plunger  
Stainless Steel, AISI 316
- Spring  
Stainless Steel AISI 316Ti
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

**3**

**Information**

Spring latches GN 722.3 are used when the indexing pin is temporarily not allowed to protrude. The indexing pin retracts by turning the latch by 180°.

**ZB**

A lock notch will hold the latch in both positions.

**SW**

Spring latches GN 722.3 are designed for use in **steel construction** or in **locksmith shops** where less precise positioning / locking is normally required. The dimensional tolerances are therefore chosen to ensure that functional safety is guaranteed under dirt exposure and that cost-effective production methods are used.

see also...

- *Range of cam action indexing plungers* → Page 712
- *Spring latches GN 722.1 (for welding)* → Page 461
- *Positioning bushings GN 412.2* → Page 454

**A4**

**How to order**

**GN 722.3-14-20-L-SW**

<b>1</b>	d <sub>1</sub>
<b>2</b>	s
<b>3</b>	Type
<b>4</b>	Colour (Finish / Material)