



EDDELSTAHL® Rostfrei
Inox Stainless Steel
Inch sizes available

- 3 Type**
- B** without rest position with plastic knob
 - BN** without rest position with Stainless Steel-Knob
 - C** with rest position with plastic knob
 - CN** with rest position with Stainless Steel-Knob

1 d₁ Plunger h9 Bore ^{+0,03} / _{-0,08}	2 d₂		d₃	d₄	l₁	l₂ min.	l₃	k	A/F	Spring load in N ≈	
	M 8	M 8 x 1								initial	end
4	M 8	M 8 x 1	21	15	27,5	5	6	16,5	10	4	12
5	M 10	M 10 x 1	25	18	34	6	8	20	12	6	16
6	M 10	M 10 x 1	25	18	34	6	8	20	12	6	16
6	M 12	M 12 x 1,5	28	20	40,5	7	10	23,5	14	10	23
7	M 12	M 12 x 1,5	28	20	40,5	7	10	23,5	14	10	23
8	M 16	M 16 x 1,5	33	23	47,5	10	12	25,5	17	11	35
10	M 16	M 16 x 1,5	33	23	47,5	10	12	25,5	17	11	35

Specification

- Socket / Plunger
Stainless Steel AISI 303
- Spring
Stainless Steel AISI 301
- Knob Type B and C
Plastic (Polyamide PA)
- black, matt
- not removable
- Knob Type BN / CN
Stainless Steel AISI CF-8
- matt blasted
- not removable
- *Stainless Steel characteristics* → Page 334
- *Plastic characteristics* → Page 334
- *ISO-Fundamental tolerances* → Page 323
- **RoHS compliant**

Accessory

- Distance bushings GN 609.5 or flat hexagonal nuts GN 909.5 are to be ordered separately.

Information

Stainless Steel-Mini indexing plungers GN 822.7 are distinguished for their small dimensions.

Based on the principle of the GN 822 mini indexing plungers, this model combines their clever type of construction with a complete series of all current sizes of bolts and threads. They provide a reasonably priced alternative to the GN 607 / GN 607.1 indexing plungers of the appropriate sizes. To mount, first turn the mini indexing plunger in with the knurled button. Pulling the indexing pin will release the hexagon nut which can then be tightened with an open-end spanner.

The spanner flats on the lock nut are revealed when retracting the pin, so that the mini indexing plunger can be easily tightened by means of a fork spanner.

In types C and CN, the button can be turned by 30° after retracting the indexing pin, holding it in the “retracted” position using the indexing lock.

see also...

- *Range of indexing plungers* → Main Catalogue Page 402 / 411

How to order	1 d₁
GN822.7-6-M12x1,5-CN	2 d₂
	3 Type