



3 Type

- S** without locking without rest position
- L1** Locking / Rest position via counterclockwise rotation
- R1** Locking / Rest position via clockwise rotation



d Plunger ^{-0.05} Bore ^{+0.1} / _{+0.06}	b ₁	b ₂	b ₃	b ₄	h ₁	h ₂	k ₁	k ₂	k ₃	k ₄	l ₁	l ₂ min.	l ₃	Spring load in N ≈	
														initial	end
6	38	32	16	5,4	8,5	6	27	5,5	12	14,5	47	10	14	21	27
8	38	32	16	5,4	8,5	6	27	5,5	12	14,5	47	10	14	21	27
8	46	40	20	6,4	11	6	33	6,5	14,5	19	59	12	17	25	38
10	38	32	16	5,4	8,5	6	27	5,5	12	14,5	47	10	14	21	27
10	46	40	20	6,4	11	6	33	6,5	14,5	19	59	12	17	25	38
12	46	40	20	6,4	11	6	33	6,5	14,5	19	59	12	17	25	38

Specification

- Housing
Zinc die casting
plastic coated, RAL 9005, textured finish
- Plunger
Steel
zinc plated, blue passivated
- Spring
Stainless Steel AISI 301
- Latch lever
Plastic, Technopolymer (Polyamide PA)
- black, matte
- not removable
- ISO-Fundamental Tolerances → Page 323
- Stainless Steel characteristics → Page 334
- Plastic characteristics → Page 331
- RoHS compliant

Information

The plunger of spring latches GN 416 is operated by an axial pulling of the latch lever. This kind of operation from the top side is advantageous in certain installation situations.

The pins of Type S spring latches are engaged in the housing to prevent rotation, and therefore lock in the starting position but not the retracted position. Types R1 and L1 spring latches offer a locking function in the starting as well as in the retracted position, preventing an unintentional operation. A lock notch holds the latch lever in both positions.

The adjustment range is designed in such a way that ISO 7092 washers can be used within the adjustment slot in the housing.

see also...

- Positioning bushings GN 412.2 → Main catalogue Page 454
- Indexing plungers GN 417 → Main catalogue Page 120 / 121

How to order

GN416-8-46-L1

- 1 d
- 2 b₁
- 3 Type