



 Inox
 Stainless
 Steel

4 Type
A with external hexagon

1 d_1	2 l_1 Nominal length	3 d_2	d_3	$d_4 +0,3$	l_2	l_3	s	Tightening torque in Nm
8	10	M 16 x 1,5	24	9,8	27,5	20	19	90
8	25	M 16	24	9,8	37,5	25	19	75
10	15	M 20 x 1,5	28	12,2	35,5	24	24	145
10	35	M 20	28	12,2	46	29	24	130
12	15	M 24 x 1,5	32	14,7	35,5	24	27	220
12	35	M 24	32	14,7	48,5	36	27	200
16	25	M 30 x 2	39	19,2	44	29	30	440
16	50	M 30	39	19,2	66	44	30	400
20	50	M 36 x 2	43	26	70	55	36	440

Specification

- Bushing
Stainless Steel
- AISI 630
- precipitation hardened
- RoHS compliant

On request

- other threads d_2

Information

Holding bushings GN 1132 are used in connection with lifting pins GN 1130. The length l_1 of the holding bushing should be equal to length l_1 of the lifting pin in order to reach the load specification given in the table for GN 1130 at plug-in length x.

Holding bushings are intended to remain permanently at the workpiece, creating a place-saving alternative to load rings or similar or similar.

How to order

GN 1132-10-35-M20-A

1 d_1
2 l_1
3 d_2
4 Type