



- 3 Type**
- A** Mounting from the back (threaded blind bore)
 - B** Mounting from the operator's side (only for b₁=20)

1 b ₁	2 l ₁ ±0,25	a	b ₂	d	h ₁	h ₂	h ₃	l ₂	l ₃	l ₄	r	t ₁ min.	t ₂
20	130	10	23	M 5	45	6,5	2,5	120	141	153	15	10	5
20	170	10	23	M 5	45	6,5	2,5	160	181	193	15	10	5
20	190	10	23	M 5	45	6,5	2,5	180	201	213	15	10	5
20	210	10	23	M 5	45	6,5	2,5	200	221	233	15	10	5
30	262	12	-	M 6	50	-	-	250	-	-	15	12	-
30	312	12	-	M 6	50	-	-	300	-	-	15	12	-
30	362	12	-	M 6	50	-	-	350	-	-	15	12	-
30	412	12	-	M 6	50	-	-	400	-	-	15	12	-

Specification

- Aluminium
 - plastic coated black, RAL 9005, textured finish ● **SW**
 - blank ○ **BL**
 - tumbled
- Handle base
 - Plastic Technopolymer (Polyamide PA) black, matt
- Load rating information → Page 1153
- RoHS compliant

Information

Cabinet handles GN 668 are produced from aluminium extrusions. They can be mounted either from the back (Type A) or by means of the handle base from the operator's side (Type B). The manufacturing process (bending) allows the production of **special lengths** in relatively small quantities.

How to order	1 b ₁
	2 l ₁
GN 668-20-170-B-SW	3 Type
	4 Finish