



3 Type

- A** Mounting from the back (Self-tapping screws)
- B** Mounting from the operators side

b₁	l₁ ±0,25	b₂	d₁	d₂	d₃	h₁	h₂	l₂	l₃ max.	l₄ min.	l₅ max.	l₆	s
12	55	12,5	M 5	4,3	12,5	40	34,5	67,5	5	14	5	10,5	9
12	88	12,5	M 5	4,3	12,5	40	34,5	100,5	5	14	5	10,5	9
12	100	12,5	M 5	4,3	12,5	40	34,5	112,5	5	14	5	10,5	9
12	120	12,5	M 5	4,3	12,5	40	34,5	132,5	5	14	5	10,5	9
12	180	12,5	M 5	4,3	12,5	40	34,5	192,5	5	14	5	10,5	9
12	235	12,5	M 5	4,3	12,5	40	34,5	247,5	5	14	5	10,5	9

Specification

- Handle bar
Aluminium

- Handle shanks
Plastic (Polyamide PA)
- glass fibre reinforced
- temperature resistant up to 130 °C

- Handle bar ● ELS
anodized, natural colour
Handle shanks
black, matt

- Handle bar ESS
anodized, black
Handle shanks
black, matt

- Handle bar ● ELG
anodized, natural colour
Handle shanks
light grey, matt

- Cylinder head screws DIN 912-M8-45
Steel zinc plated, black

- Flange nuts DIN 1661-M5
Steel zinc plated, blue passivated

- Self-tapping screws ISO 7049
Steel zinc plated ST4,8-19

- RoHS compliant



Information

The dimensions of the „U“ handles GN 423 have been designed to match a 19“ rack and enclosure layout.

Handle bar and handle shanks are interconnected via a plug-type connection, with the effect that special lengths are easily realised.

Thanks to the fixing screws included in the set, the „U“ handles are easily and economically mounted.

see also...

- Cabinet „U“ handles GN 627
- Cabinet „U“ handles GN 425 → Page 80
- Cabinet „U“ handles GN 425.6 → Page 80
- Cabinet „U“ handles GN 427 → Page 91
- Stainless Steel-Cabinet „U“ handles GN 427.5 → Page 91

How to order

GN423-12-120-A-ELS

- 1** b₁
- 2** l₁
- 3** Type
- 4** Finish