



2

3

d ₁	d ₂	b	d ₃ ^{+0.2 +0.5}	Length l	m	s	t	Countersunk screw DIN 7991	for cabinet „U“ handles
8	M 4	10	4	20	10	3	7	M 4 x 10	GN 425-8-...
10	M 5	12	5	24	12	4	8	M 5 x 12	GN 425-10-... / GN 425.1-10-...
12	M 6	15	6	30	15	4,5	9,5	M 6 x 14	GN 425-12-... / GN 425.1-12-...
16	M 6	18	6	34	16	4,5	9,5	M 6 x 14	GN 425-16-...
20	M 6	22	6	40	18	4,5	9,5	M 6 x 14	GN 565-20-... / GN 565.5-20-...
20	M 8	22	8	42	20	6	12	M 8 x 18	GN 426-20-... / GN 426.1-20-...
26	M 8	28	8	52	24	6	12	M 8 x 18	GN 565-26-...
28	M 10	30	10	56	26	6,5	13,5	M 10 x 20	GN 426-28-... / GN 426.1-28-...

Specification

1

4

- Zinc die casting **ZD**
plastic coated
black, RAL 9005, textured finish ● **SW**
silver, RAL 9006, textured finish ● **SR**
- Countersunk screws
DIN 7991
Steel zinc plated, blue passivated
- RoHS compliant

Information

Fastening sets GN 181 make it possible to mount different cabinet „U“ handles and tubular handles with internal thread from the operator's side.

The mounting position of the fastening plates is freely customizable, allowing a sideways offset or mounting with different drillhole spacings.

A fastening set consists of 2 fastening plates and 2 countersunk screws.

see also...

- Assembly sets for profile systems 30 / 40 GN 965 → Page 145
- Assembly sets for profile systems 30 / 40 / 45 GN 968 → Page 153

How to order

1	Material
2	d ₁
3	d ₂
4	Finish

GN 181-ZD-28-M10-SW