



 Inch sizes available

| ¹ l ₁ | ² d ₁ Thread | | | ² d ₂ H7 Bore | | d ₃ | d ₄ | h ₁ | h ₂ | h ₃ | h ₄ Stroke | t min. |
|-----------------------------|------------------------------------|------|-----|-------------------------------------|------|----------------|----------------|----------------|----------------|----------------|-----------------------|--------|
| 30 | M 3 | - | - | - | - | 10 | 13 | 24,5 | 4 | 22 | 3,5 | 7 |
| 30 | M 4 | M 5 | M 6 | B 5 | B 6 | 10 | 13 | 24,5 | 4 | 22 | 3,5 | 9 |
| 45 | M 4 | M 5 | M 6 | B 5 | B 6 | 10 | 13 | 24,5 | 4 | 22 | 3,5 | 9 |
| 63 | M 6 | M 8 | - | B 8 | - | 13,5 | 17,5 | 31 | 6,5 | 28,5 | 4 | 11 |
| 78 | M 8 | M 10 | - | B 8 | B 10 | 16 | 21 | 36 | 8 | 34 | 4 | 14 |

Specification

- Handle
Zinc die casting
- plastic coated
black, RAL 9005, textured finish ● **SW**
orange, RAL 2004, textured finish ● **OS**
red, RAL 3000, textured finish ● **RS**
silver, RAL 9006, textured finish ● **SR**
- Threaded bush and retaining screw
Steel, blackened
- ISO-Fundamental Tolerances → Page 1132
- RoHS compliant

On request

- with insert in Stainless Steel
- with push-button

Information

Adjustable hand levers GN 302 have a straight lever, not inclined, being parallel to the clamping space.

Adjustable hand levers are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swivelled to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

How to order

¹ ² ³
GN 302-45-M4-SR

| | |
|---|----------------------------------|
| 1 | l ₁ |
| 2 | d ₁ (d ₂) |
| 3 | Colour (Finish) |