



3 Type

- D straight lever
- E angled lever

1

2

d ₁	d ₂ Thread			d ₃	d ₄	d ₅	h ₁	h ₂	h ₃	h ₄ ≈	h ₅ Stroke	l	t min.
32	M 6	M 8	-	13,5	8	20	20,5	1,5	12,5	36	4	100	11
36	M 8	M 10	M 12	16	10	25	24,5	2	15	45	4,5	120	14
40	M 10	M 12	-	19	12	30	26,5	2	16	50	4,5	130	17
45	M 12	M 14	M 16	23	12	32	31,5	2	20	60	5	145	23

Specification

- Steel blackened
Threaded insert
Tensile strength class 5.8 (500 N/mm²)
- Plane surface with natural coloured, anodized Aluminium disc
- Ball knobs DIN 319
Plastic, Duroplast
black, shiny finish
- RoHS compliant

On request

- with threaded through hole

Information

The overall height of flat tension levers GN 125 is reduced to a minimum. As all other adjustable levers, they are ideal whenever parts have to be clamped in a confined space, or a particular lever position is required. The threaded insert is connected with the hub via serrations which can be disengaged.

Pulling the lever, disengages the serrations and the lever can be swivelled to the ideal clamping position. On releasing the lever it will automatically re-engage.

see also...

- *Adjustable Stainless Steel-Flat tension levers GN 125.5* → Page 232

How to order

GN 125-32-M8-D

- | | |
|---|----------------|
| 1 | d ₁ |
| 2 | d ₂ |
| 4 | Type |