



**2 Type**

- A without dowel hole
- B with dowel hole



<b>d<sub>1</sub></b> Thread	<b>d<sub>2</sub></b> H7 Bore	<b>d<sub>3</sub></b>	<b>d<sub>4</sub></b>	<b>d<sub>5</sub></b> H11	<b>e</b>	<b>h</b>	<b>k</b>	<b>l</b>
M 5	B 5	14	20	1,5	2,5	12	8	7
M 6	B 6	16	24	1,5	2,5	14	10	8
M 8	B 8	20	30	2	3	17	12	10
M 10	B 10	28	36	3	4	20	14	12
M 12	B 12	32	40	4	4	24	16	16

**Specification**

- Steel
  - Tensile strength class 5 (500 N/mm<sup>2</sup>)
  - blackened
- ISO-Fundamental Tolerances → Page 1132
- RoHS compliant

**Information**

The dowel bore  $d_5$  in the DIN 6303 knurled nut is designed for the use of clamping or notch pins.

DIN 6303 knurled nuts with H7 bore and the size M12 are not provided for on the official standard sheet.

see also...

- Quick release-Knurled nuts GN 6303.1 → Page 324

How to order

**DIN 6303-M8-A**

**1** **d<sub>1</sub>** (d<sub>2</sub>)

**2** **Type**