



**2 Bore code**  
**B** without keyway  
**K** with keyway  
**V** with square

<b>1</b> $d_1$	<b>3</b> $d_2$ H9 Bore	$s$ H11 Square	$b$	$d_3$	$l_1$	$l_2 \approx$	No. of spokes	Thickness of pressed steel
125	11	V 11	18	30	18	29	3	1,5
160	12	V 12	22	30	20	37	4	1,5
200	14	V 14	22	40	24	46	4	2,5
250	17	V 17	30	45	28	52	5	2,5
315	19	V 19	35	55	33	64	5	2,5
400	24	V 24	40	65	38	82	5	3

**Specification**

- Pressed Steel plastic coated black, textured finish **SW**
- Hub Steel, welded
- Keyway P9 DIN 6885 → Page 1124
- Square DIN 79 → Page 1126
- Cross hole GN 110 → Page 1127
- ISO-Fundamental Tolerances → Page 1132
- RoHS compliant

**On request**

- with conical square VK
- with revolving handle

**4**

**Information**

The hub lengths of the pressed steel handwheels GN 227.1 conform to DIN 950.

Pressed steel handwheels GN 227.1 are renowned for their high mechanical strength. They are not affected by shock and knocks.

see also...

- Stainless Steel-Handwheels GN 227.2 → Page 189
- Countersunk washers GN 184 (for axial fixing) → Page 542

How to order

**GN 227.1-200-V14-SW**

- 1**  $d_1$
- 2** Bore code
- 3**  $d_2$  (s)
- 4** Colour