



- 1 Type**
- SC** Operation with key (same lock)
 - SU** with key (different lock)
 - SCK** with wrench (same lock)
 - SUK** with wrench (different lock)
 - SCT** with T-Handle (same lock)
 - SUT** with T-Handle (different lock)

- 3 Version of the hook**
- H1** Pivot radius R=28

- 5 Identification no.**
- 1** without latch bracket
 - 2** with latch bracket

2

Latch distance A	d		h	
	Type SC, SU	Type SCK, SUK, SCT, SUT	Type SC, SU	Type SCK, SUK, SCT, SUT
18	28	32	4	6

1) Dimensions of the latch bracket → Page 243

Specification

- Lock housing
Zinc die casting
- Locating ring
 - chrome plated **CR**
 - plastic coated black, RAL 9005, textured finish **SW**
- All other parts
Steel zinc plated, blue passivated
- Key
Nickel silver with plastic hand piece
- Wrench / T-Handle
Plastic (Polyamide PA) black, matt
- **RoHS compliant**

On request

- Hook-type latches with other hook distance A
- Hook with other pivoting radius R

4

Information

Hook-type latches GN 115.8 with hook and latch bracket are mainly used for sliding doors and flaps. The locking action is in radial direction to the axis of rotation, resulting in a wide variety of different uses.

Two keys are supplied with the unit. The key can be removed in both end positions.

Hook-type latches GN 115.8 are supplied with the hook enclosed loose.

Further construction and assembly instructions → Page 243.

see also...

- *Hook-type latches GN 115.8 (Operation with key) → Page 242*

How to order

1 Type
2 Latch distance A
3 Version of the hook
4 Finish locating ring
5 Identification no.

GN 115.8-SC-18-H1-SW-1