



- 1** Type
- SC** Operation with key (same lock)
- SU** Operation with key (different lock)
- 3** Identification no.
  - 1** Operation, in drawn position, at the top left
  - 2** Operation, in drawn position, at the top right

**2**

Latch distance <b>A</b>																					
4	6	8	10	13	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	45	50

**Specification**

- Front frame
  - Zinc die casting
  - plastic coated
  - black, RAL 9005, textured finish
  - silver, RAL 9006, textured finish
- Tray
  - Plastic
  - black grey (for SW)
  - light grey (for SR)
- Key
  - Nickel silver with plastic hand piece
- other parts
  - Steel
  - zinc plated, blue passivated
- **RoHS compliant**

● **SW**  
● **SR**

**4**

**Information**

Latches with gripping tray GN 115.10 are used in applications which require a moulded recess in addition to the latching mechanism, e.g. if operating elements are not allowed to protrude for reasons of space.

A rotary movement limited to 90° moves the latch behind the frame, with the run-up bevels at the latch making it easier to close the door.

Latches with 22 different cranks cover a latch distance A from 4 to 50 mm.

Latches GN 115.10 are supplied with loosely enclosed locking.

**see also...**

- Latches with cabinet „U“ handles GN 115.7 → Main catalogue Page 866

How to order	1	Type
	2	Latch distance A
	3	Identification no.
<b>GN 115.10-SC-20-2-SW</b>	4	Finish