


**4 Identification No.**

2 with 4 Stainless Steel-Clamping screws DIN 912



<b>1</b> $d_1$ Bore B	<b>1</b> $s_1$ Square V	<b>2</b> $d_2$ Bore B	<b>2</b> $s_2$ Square V	<b>3</b> $k_1$ Clamping length	$k_2$ Clamping length	$d_3$ Clamping thread	$d_4$ Clamping thread	$l_1$	$l_2$	$l_3$	$m$	Clamping kits	
												for $d_3$	for $d_4$
B 30	V 30	B 40	V 40	60	76	M 8	M 10	120	79	98	55	GN 911-M8-55	GN 911-M10-55
B 30	V 30	B 48	-	60	76	M 8	M 10	120	79	98	55	GN 911-M8-55	GN 911-M10-55
B 30	V 30	B 50	V 50	60	76	M 8	M 10	120	79	98	55	GN 911-M8-55	GN 911-M10-55
B 40	V 40	B 48	-	60	76	M 8	M 10	120	79	98	55	GN 911-M8-55	GN 911-M10-55
B 40	V 40	B 50	V 50	60	76	M 8	M 10	120	79	98	55	GN 911-M8-55	GN 911-M10-55

**Specification**

- Aluminum
  - plastic coated
  - black, RAL 9005, textured finish **● SW**
  - blank **○ BL**
  - matt shot-blasted
- Clamping bores not machined
- Cap screws DIN 912  
Stainless Steel AISI 304
- Hexagon nuts DIN 985  
Stainless Steel AISI 304
- Stainless Steel characteristics → Page 1144
- RoHS compliant

**Accessory**

- Clamping kits GN 911

**On request**

- other bore and square combinations  $d_1 / s_1$  and  $d_2 / s_2$

**5 Information**

The clamping bores of GN 135 two-way connector clamps are not machined and specially designed for construction tubings GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The square designs are also suitable for use in **profile systems**.

The bore holes and squares must be put together such that an adaptation between different tube cross-sections is possible.

The standard version of the clamping screws are socket cap screws with hexagonal socket DIN 912. They can be replaced by clamping kits GN 911 (article code see table of dimensions).

see also...

- Two-way connector clamps GN 134 → Page 980
- Construction tubes GN 990 → Page 1027

How to order

<b>1</b>	$d_1$ ( $s_1$ )
<b>2</b>	$s_2$ ( $d_2$ )
<b>3</b>	$k_1$
<b>4</b>	Identification No.
<b>5</b>	Finish

**GN 135-B30-V40-60-2-SW**