



Assembly set for slot width 8  
2x T-Nut GN 505  
2x Socket head cap screw DIN 7984




Assembly set for slot width 10  
2x T-Slot bolt GN 505.4  
2x Flange nut DIN 6923



5 Type

- A without assembly set, without cover
- B with assembly set, with cover
- C with assembly set, without cover



1

2

3

4

b <sub>1</sub>		n	l <sub>1</sub>	l <sub>2</sub>	b <sub>2</sub>	h	l <sub>3</sub>	l <sub>4</sub>	l <sub>5</sub>	l <sub>6</sub>	s
Nominal size	Actual size										
30	28	8	30	30	6,3	2,1	3	9,7	10,4	6,8	5,9
40	38	10	40	40	8,5	4,1	4	9,5	20	7,2	5,6
45	43	10	45	45	8,5	4,1	4	15,7	18,7	11,5	9,7

Specification

- Aluminium Die casting
  - matt shot-blasted **MT**
  - plastic coated
    - **SW** black, RAL 9005, textured finish
    - **SR** silver, RAL 9006, textured finish
- T-Slot bolt GN 505.4 with hexagon flange nut DIN 6923 Steel zinc plated, blue passivated
- T-Nut GN 505 with socket head cap screw DIN 7984 Steel zinc plated, blue passivated
- Cover Plastic (Polyamide PA) black, matt
- RoHS-compliant

6

Information

To fix the angle pieces GN 960 in place, insert the assembly sets into the profile slot through the opening. When tightened, the nut or screw will be cross-positioned and so anchored in the slot.

For crossing profiles or when using the angle piece with elements without slot, the superfluous guide steps can be simply broken out.

After assembly, the cover caps are snapped into place via four lugs. They lend the angle piece an attractive appearance and protect against dirt.

Even after repeated use, the cover caps will remain firmly in place inside the angle pieces thanks to the elastic snap-type lugs. If required, these are also available individually under standard GN 963.

see also...

- T-Slot bolts GN 505.4 → Page 566
- T-Nuts GN 505 → Page 567

How to order

1	b <sub>1</sub>
2	n
3	l <sub>1</sub>
4	l <sub>2</sub>
5	Type
6	Finish

**GN 960-45-10-45-45-A-SW**