



d	Square s₀	s₁ -0,1	s₂ -0,1	l₁ ±0,5	l₂	l₃ -1	No. of spokes
50	V 6	5,8	6,15	9	15,5	8	3
50	V 7	6,8	7,15	9	15,5	8	3
60	V 6	5,8	6,15	9	16,5	8	3
60	V 7	6,8	7,15	10	17,5	9	3
70	V 7	6,8	7,15	10	19	9	3
70	V 8	7,8	8,15	10	19	9	3
80	V 8	7,8	8,15	11	20	10	3
80	V 9	9,0	9,15	12	20	11	3
90	V 9	8,8	9,15	12	24	11	3
100	V 9	9,0	9,20	13	24	12	4
100	V 10	9,8	10,20	13	24	12	4
120	V 11	11,0	11,20	14	31	13	4
120	V 12	12,0	12,25	16	32,5	14	4
140	V 12	12,0	12,25	16	32,5	14	4
160	V 14	14,0	14,25	20	37	18	4

Specification

- Pressed Steel plastic coated black, RAL 9005 red, RAL 3000 uncoated

- SW
- RT
- RH

- RoHS compliant

Information

Pressed steel handwheels GN 227 have been specially developed for valves and they offer definite advantages:

They consist of a single unwelded piece of pressed sheet metal manufactured by a special process to give a re-inforced hub. They offer high mechanical strength and are not affected by shocks and knocks.

They are resistant to temperature and fire and not weakened by any ageing process.

The slightly tapered square hole allows easy installation and firm seating on a spindle.

How to order

GN 227-60-V7-SW

1	d
2	s₀
3	Colour