



Internationaler Designpreis Baden-Württemberg

2 Bore code

- B without keyway
- K with keyway

4 Type

- A without handle
- R with revolving handle

1

3

d ₁	d ₂ H7 Bore		d ₃	b	l ₁	l ₂	l ₃	r	Ø Handle GN 798
125	12	14	31	15	18	33	61,5	54	22
140	14	16	36	16,5	19	36	76,5	61	24
160	14	16	36	18	20	39	76,5	71	24
200	18	20	42	20,5	24	45	86,5	89	25
250	22	26	48	23	28	51	86,5	113	25

Specification

- Aluminium
 - Hub machined
 - Rim turned
- Rim concentric and square to bore < 0,4
- **GN 322**
 - Rim high-polished
 - unmachined body matt shot-blasted
- **GN 324**
 - Body plastic coated
 - black, textured finish
- Revolving handles GN 798
 - Plastic, Technopolymer
 - black, matt
- Keyway P9 DIN 6885 → Page 1124
- Cross holes GN 110 → Page 1127
- ISO-Fundamental Tolerances → Page 1132
- RoHS compliant

Information

- see also...
- Safety handwheels (disengage the clutch) → Page 168
 - Countersunk washers GN 184 (for axial fixing) → Page 542

Spoked handwheel, polished

1 2 3 4
GN322-140-K14-R

- 1 d₁
- 2 Bore code
- 3 d₂
- 4 Type

Spoked handwheel, black

1 2 3 4
GN324-200-B20-A

- 1 d₁
- 2 Bore code
- 3 d₂
- 4 Type