



**3 Type**

- K** Straight lever with plain bore H7 (only  $l_1 = 50$  to  $160$ )
- M** Straight lever with threaded bore (only  $l_1 = 50$  to  $160$ )
- L** Angled lever with plain bore H7
- N** Angled lever with threaded bore

<b>1</b> $l_1$	<b>2</b> $d_1$ Thread	<b>2</b> $d_2$ H7 Bore	<b>b</b>	$d_3$	$d_4 \approx$	$d_5 -0,2$	$h \approx$	$l_2 \approx$
50	M 6	B 6	9,5	8	7,5	12	24	48
63	M 8	B 8	12	10	11	16	30	60
80	M 10	B 10	14,5	13	15	20	38	76
100	M 12	B 12	18,5	16	19	25	47	95
125	M 16	B 16	24	20	23,5	32	59,5	119
160	M 20	B 20	30	25	29,5	40	76	152
200	M 24	B 24	40	32	33	50	97	190

**Specification**

- Steel
  - turned
  - blackened
- ISO Fundamental Tolerances → Page 1132
- RoHS compliant

**Information**

The official DIN standard sheet specifies additional sizes 40 - M5 / B5.

see also...

- Short clamping levers GN 204 → Page 246
- Clamp nuts GN 99.5 (welded) → Page 248
- Adjustable clamping levers GN 99.2 → Page 234

How to order

**DIN 99-100-M12-N**

- 1**  $l_1$
- 2**  $d_1$  ( $d_2$ )
- 3** Type