



3 Type

- A** without plastic cover
- B** with plastic cover

1 **2**

d₁ Plunger Bore H7	d₂	d₃	h	k	l₁	l₂	l₃	l₄	s	Spring load in N ≈	
										initial	end
6	16	35	16	20	56	10	32	42	12	12	32
8	16	35	16	20	56	10	32	42	12	12	32
8	20	40	20	22	69	12	37	52	15	21	58
10	16	35	16	20	56	10	32	42	12	12	32
10	20	40	20	22	69	12	37	52	15	21	58
12	20	40	20	22	69	12	37	52	15	21	58

Specification

- Steel
 - blackened
 - Plunger nitrided
- Plastic cover (Polyamide PA)
 - black, matt
- ISO-Fundamental Tolerances → Page 1132
- RoHS compliant

Information

Cam action indexing plungers GN 612.2 are used in cases where the locking pin must not protrude all the time. By rotating the lock through 180° the locking pin withdraws itself. A notch keeps the plunger in this position.

see also...

- Range of cam action indexing plungers → Page 412
- Positioning bushings GN 412.2 → Page 454

How to order

GN612.2-8-16-B

1	d₁
2	d₂
3	Type

2.1
2.2
2.3
2.4
2.5
2.6
2.7
2.8
2.9