



Rost free
 Inox Stainless Steel
 Inch sizes available

- 3 Identification No.**
- 2** with two Stainless Steel-Clamping screw DIN 912

1

2

d ₁ Bore B		d ₂ Bore B		d ₃ Clamping thread	k Clamping length	l ₁	l ₂	m	Clamping kit for d ₃	
Aluminum	Stainless Steel	Aluminum	Stainless Steel						Lever Zinc die casting	Lever Stainless Steel
B 10	-	B 10	-	M 6	25	61	34,5	39	GN 911-M6-22	GN 911.3-M6-22
B 12	B 12	B 12	B 12	M 6	25	61	34,5	39	GN 911-M6-22	GN 911.3-M6-22
B 14	B 14	B 14	B 14	M 6	25	61	34,5	39	GN 911-M6-22	GN 911.3-M6-22
B 15	B 15	B 15	B 15	M 6	25	61	34,5	39	GN 911-M6-22	GN 911.3-M6-22
B 16	B 16	B 16	B 16	M 6	25	61	34,5	39	GN 911-M6-22	GN 911.3-M6-22
B 18	B 18	B 18	B 18	M 6	25	61	34,5	39	GN 911-M6-22	GN 911.3-M6-22
-	B 20	-	B 20	M 6	25	61	34,5	39	GN 911-M6-22	GN 911.3-M6-22

Specification

4

- Aluminum
 - plastic coated black, RAL 9005, textured finish ● **SW**
 - blank ○ **BL**
 - blank matt shot-blasted
- Stainless Steel **NI**
 - AISI CF-8
 - blank matt shot-blasted
- Clamping bores mechanically machined
- Socket cap screws DIN 912 Stainless Steel AISI 304
- Hexagon nuts DIN 985 Stainless Steel AISI 304
- RoHS compliant

Accessory

- Clamping kits GN 911 / GN 911.3
→ Page 1031

On request

- d₁ / d₂ with different bores

Information

The clamping bores of the T-Angle connector clamps GN 191 are mechanically machined and designed for construction tubes GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The standard version of the clamping screws are socket cap screws with hexagonal socket DIN 912. They can be replaced by clamping kits GN 911 / GN 911.3 (article code see table of dimensions).

see also...

- Construction tubes GN 990 → Page 1027
- T-Angle linear actuator connectors GN 191.1 → Page 1052

How to order (Aluminum)

1	d ₁
2	d ₂
3	Identification No.
4	Finish

GN 191-B12-B12-2-SW

How to order (Stainless Steel)

1	d ₁
2	d ₂
3	Identification No.
4	Material

GN 191-B16-B16-2-NI