



1 2 3

l ₁	l ₂	d ₁	b	a		Type PR / Type RF		d ₂ Ø	h ₁ ≈	h ₂	Length l ₃ max.	for wedge clamps GN 920.1 with:	
				Type GA / Type GL max.	Type GL min.	max.	min.					d	b
25	32	M 8	21	44,5	39,5	39,5	34,5	18	27,5	4	7,5	M 8	21
29	32	M 8	25	44,5	39,5	39,5	34,5	18	27,5	4	7,5	M 8	25
36	32	M 8	32	44,5	39,5	39,5	34,5	18	27,5	4	7,5	M 8	32
44	32	M 8	40	44,5	39,5	39,5	34,5	18	27,5	4	7,5	M 8	40
44	32	M 12	40	45,5	40	45,5	40	23	38	5	11,5	M 12	40
54	32	M 8	50	44,5	39,5	39,5	34,5	18	27,5	4	7,5	M 8	50
54	32	M 12	50	45,5	40	45,5	40	23	38	5	11,5	M 12	50

Specification

- Steel blackened
- Socket head cap screw DIN 912 (ISO 4762) Tensile strength class 12.9 (1200 N/mm²)
- Distance sleeve Steel
- RoHS compliant

Information

Pull-down plates GN 920.2 allow wedge clamps GN 920.1 to clamp easily with pull-down effect.

The socket head cap screw DIN 912 and the distance bush are included.

see also...

- *Wedge clamps GN 920.1* → Page 660

How to order

GN920.2-36-32- M8

1	l ₁
2	l ₂
3	d ₁