



**4 Type (Base plate)**

**A1** Steel, zinc plated  
Rubber, inlaid, black

1		2		3							3					
d <sub>1</sub>	d <sub>2</sub>	l <sub>1</sub>					Version U / UK					l <sub>7</sub>	h <sub>1</sub>	d <sub>4</sub>	l <sub>8</sub>	l <sub>9</sub>
		Version S / SK										Version X				
50	M 8	40	50	63	-	-	-	-	-	-	40	18	13	25	45	
50	M 10	50	60	80	100	-	-	-	-	-	43	18	13	25	45	
50	M 12	60	80	100	125	-	-	-	-	-	47	18	13	25	45	
50	M 16	-	-	-	-	75	100	125	150	200	52	18	13	25	45	
60	M 8	40	50	63	-	-	-	-	-	-	41	19	13	25	50	
60	M 10	50	60	80	100	-	-	-	-	-	44	19	13	25	50	
60	M 12	60	80	100	125	-	-	-	-	-	48	19	13	25	50	
60	M 16	-	-	-	-	75	100	125	150	200	53	19	13	25	50	
80	M 8	40	50	63	-	-	-	-	-	-	42	20	13	30	70	
80	M 10	50	60	80	100	-	-	-	-	-	45	20	13	30	70	
80	M 12	60	80	100	125	-	-	-	-	-	49	20	13	30	70	
80	M 16	-	-	-	-	75	100	125	150	200	54	20	13	30	70	
80	M 20	-	-	-	-	75	100	125	150	200	62	20	13	30	70	
80	M 24	-	-	-	-	100	125	150	200	-	-	20	13	30	70	
100	M 8	40	50	63	-	-	-	-	-	-	43	21	13	30	80	
100	M 10	50	60	80	100	-	-	-	-	-	46	21	13	30	80	
100	M 12	60	80	100	125	-	-	-	-	-	50	21	13	30	80	
100	M 16	-	-	-	-	75	100	125	150	200	55	21	13	30	80	
100	M 20	-	-	-	-	75	100	125	150	200	63	21	13	30	80	
100	M 24	-	-	-	-	100	125	150	200	-	-	21	13	30	80	

**Specification**

- Base plate / lug, sheet metal  
Steel, zinc plated, blue passivated
- Threaded stem  
Steel, zinc plated, blue passivated
- Hexagon nut ISO 4032  
Steel, zinc plated, blue passivated
- Rubber underlay, inlaid  
black, Perbunan® (NBR)  
80±5 Shore A
- Elastomer characteristics → Page 330
- Load rating information → Page 231
- RoHS compliant

**Versions of threaded stem**

<p><b>5</b>  <b>S</b> without nut  <b>SK</b> with nut</p>	<p><b>5</b>  <b>U</b> without nut  <b>UK</b> with nut</p>	<p><b>5</b>  <b>X</b> with female thread</p>
<p>External hexagon at the bottom  M 8, M 10, M 12</p>	<p>Hexagon socket at the top  Wrench flat at the bottom  M 16, M 20, M 24</p>	<p>External hexagon  Female thread  M 8, M 10, M 12, M 16, M 20</p>

d <sub>1</sub>	d <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	A/F <sub>1</sub>	A/F <sub>2</sub>	A/F <sub>3</sub>	A/F <sub>7</sub>	t
50	M 8	26	-	17	-	-	14	8
50	M 10	26	-	17	-	-	14	10
50	M 12	26	-	17	-	-	17	12
50	M 16	-	32	-	12	8	22	16
60	M 8	27	-	17	-	-	14	8
60	M 10	27	-	17	-	-	14	10
60	M 12	27	-	17	-	-	17	12
60	M 16	-	33	-	12	8	22	16
80	M 8	28	-	17	-	-	14	8
80	M 10	28	-	17	-	-	14	10
80	M 12	28	-	17	-	-	17	12
80	M 16	-	34	-	12	8	22	16
80	M 20	-	35	-	15	10	27	20
80	M 24	-	38	-	19	12	-	-
100	M 8	29	-	17	-	-	14	8
100	M 10	29	-	17	-	-	14	10
100	M 12	29	-	17	-	-	17	12
100	M 16	-	35	-	12	8	22	16
100	M 20	-	36	-	15	10	27	20
100	M 24	-	39	-	19	12	-	-

**Information**

Levelling feet GN 32 will be delivered mounted and are not removable.

see also...

- *Stainless Steel-Levelling feet GN 33 (with fixing lug) → Page 224*
- *Levelling feet GN 30 (Steel, zinc plated, without fixing lug) → Page 218*

How to order		1	d <sub>1</sub>
		2	d <sub>2</sub>
		3	h <sub>1</sub> (h <sub>7</sub> )
		4	Type (Base plate)
		5	Version (Stem)

**GN 32-100-M20-150-A1-U**