



### 3 Type

- A** Mounting from the back (threaded blind bore)  
**B** Mounting from the operator's side

1

2

$d_1$	$l_1 \pm 0,5$ Type A	$\pm 0,3$ Type B Threaded bore for mounting stud	$d_2$	$d_3$	$h_1$	$h_2$	$l_2$	$r$	$t_1$	$t_2$
20	200	200	M 8	-	105	68	20	22	15	-
20	300	300	M 8	-	105	68	20	22	15	-
28	250	250	M 10	32	128	90	20	32	-	17
28	350	350	M 10	32	128	90	20	32	-	17
28	500	500	M 10	32	128	90	20	32	-	17

## Specification

- Stainless Steel  
 $d_1 = 20$ : solid material  
 $d_1 = 28$ : tube  $\varnothing 28 \times 2$   
 - AISI 304  
 - matt shot-blasted
- Threaded bushing / Mounting stud  
 Stainless Steel AISI 303
- Grub screw (type B)  
 $d_1 = 20$ : DIN 914-M5-6-NI  
 $d_1 = 28$ : DIN 914-M6-8-NI
- Stainless Steel characteristics → Page 334
- RoHS compliant

## Information

Stainless Steel-Cabinet „U“ handles GN 426.6 can be mounted from the back (type A) as well as from the operator's side (type B). In this case the stud is first screwed in from the machine side and then the handle is pushed on and secured with the grub screw.

Both mounting methods allow the mounting of a pair of handles in opposite position. This method could be used e.g. on doors (double handle). In general, a mounting stud with special length  $l_2$  might be required.

The manufacturing process (bending) allows the production of **special lengths** in relatively small quantities.

see also...

- Cabinet „U“ handles GN 425.1 (Aluminium / Stainless Steel, angled)  
 → Main catalogue page 86

How to order

GN 426.6-20-300-A

1  $d_1$   
 2  $l_1$   
 3 Type