



<sup>1</sup> l <sub>1</sub>	<sup>2</sup> d <sub>1</sub>	d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>3</sub>	h <sub>4</sub> Stroke	t min.
63	M 6	24	17,5	34,5	48,5	4	12,5
78	M 8	25	21	39,5	58,5	4	14
92	M 10	30	24	46,5	68,5	4	18
108	M 12	35	30	56,5	82	5	26,5

**Specification**

- Handle  
Zinc die casting
- plastic coated  
black, RAL 9005, textured finish ● **SW**  
black, RAL 9011, silk finish ● **SZ**  
orange, RAL 2004, textured finish ● **OS**  
red, RAL 3000, textured finish ● **RS**  
silver, RAL 9006, textured finish ● **SR**
- chrome-plated ● **CR**
- Bushing  
Steel  
- Tensile strength class 5  
- nitrided, blackened
- Retaining screw  
Steel, blackened
- RoHS compliant

**Information**

Adjustable hand levers GN 300.4 are produced with a clamping area which is linked via a thrust ball bearing to the bushing and screw respectively of the clamping lever. This has led to the following advantages:

- **Doubled** clamping force through vastly reduced friction.
- There is no movement on the contact area between adjustable hand lever and component which greatly reduces any marking on the clamping area.
- In addition a reduced creep factor has been achieved by the increased preload.

How to order	<sup>1</sup>	l <sub>1</sub>
	<sup>2</sup>	d <sub>1</sub>
	<sup>3</sup>	Color (Finish)
<b>GN 300.4-78-M8-SW</b>		